

Specification Sheet

Part Number: 173-61600

The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling.

The special combination of tin-plated copper and PBTV0 yarn offers optimal inside and outside abrasion resistance.

In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.



Electromagnetic Protection Braided Sleeving, Flame Retardant, 16 mm Dia, PET;TNCU, TCBK, 328ft/Reel

Article Number	173-61600
Type	HEGEMIPV016
Color	Tin-coloured and Black (TCBK)
Quantity Per	metre
Product Description	HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.
Short Description	Electromagnetic Protection Braided Sleeving, Flame Retardant, 16 mm Dia, PET;TNCU, TCBK, 328ft/Reel

Global Part Name	HEGEMIPV016-PBT/SNCU-SR
Length L (Imperial)	328.0
Length L (Metric)	100.0
Bundle Diameter Min (Imperial)	0.55
Bundle Diameter Min (Metric)	14
Bundle Diameter Max (Imperial)	0.79
Bundle Diameter Max (Metric)	20
Diameter D (Imperial)	0.59
Diameter D (Metric)	16
Nominal Diameter (Imperial)	0.63
Nominal Diameter (Metric)	16
Material	Polyester (PBT) Tin-plated copper (SNCU)
Material Shortcut	PBT SNCU
Flammability	UL 94 V-0 FMVSS 302

Halogen Free	No
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	328
Package Quantity (Metric)	100
Customs Number	5808100000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)