

Specification Sheet

Part Number: 111-01670



Very high heat resistance up to 200°C (392°F).

PAEK material has double the tensile strength than nylon.

PAEK material offers very good chemical resistance against hydrocarbons.

High-Temp Cable Tie, 5.9" Long, 100lb Tensile Strength, PAEK, Beige, 100/pkg

Article Number 111-01670

Type PAT100R

Color Beige (BGE)

Quantity Per bag

Product Description HellermannTyton PAEK cable ties offer very high temperature resistance for use in demanding applications such as in engine compartments, near exhaust, and in enclosed industrial cabinets. The PAEK ties are inside serrated and feature a high performance design that, along with the material, offer extremely high tensile strength for tough applications.

Short Description High-Temp Cable Tie, 5.9" Long, 100lb Tensile Strength, PAEK, Beige, 100/pkg

Global Part Name PAT100R-PAEK-BGE

Minimum Tensile Strength (Imperial) 100.0

Minimum Tensile Strength (Metric) 445.0

Length L (Imperial) 5.9

Length L (Metric) 149.9

Width W (Imperial) 0.33

Width W (Metric) 8.0

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Material Polyaryletherketone (PAEK)

Material Shortcut PAEK

Flammability UL 94 V-0

Operating Temperature -67°F to +392°F (-55°C to +200°C)

ROHS Compliant Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988