

## Specification Sheet

Part Number: 133-00285



Tubes are fixed a defined distance from the substructure.  
Defined diameter for the wire entry.

Retainer is fixed in the hole with BHT-tie.

Cable Guide Standoff, 1.0" Max Bundle Diameter, PA66HIRHS, Black, 150/pkg

|                |           |
|----------------|-----------|
| Article Number | 133-00285 |
|----------------|-----------|

|      |      |
|------|------|
| Type | CGS2 |
|------|------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |        |
|--------------|--------|
| Quantity Per | carton |
|--------------|--------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | This cable guide standoff is designed for the use with HellermannTyton's button head ties. The cable guide standoff stands off bundles from frame rails, providing clearance from bolts and other protrusions for protection against abrasion. This mount also allows the flow-through of salt, dirt and other impurities from the road, preventing unwanted build-up on hoses and harnesses. This product perfectly secures convoluted tubing's up to 26mm in diameter. |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                           |
|-------------------|---------------------------------------------------------------------------|
| Short Description | Cable Guide Standoff, 1.0" Max Bundle Diameter, PA66HIRHS, Black, 150/pkg |
|-------------------|---------------------------------------------------------------------------|

|                                                |                                                                  |
|------------------------------------------------|------------------------------------------------------------------|
| <b>Global Part Name</b>                        | CGS2-PA66HIRHS-BK                                                |
| <b>Length L (Imperial)</b>                     | 3.23                                                             |
| <b>Length L (Metric)</b>                       | 82.04                                                            |
| <b>Variant</b>                                 | Mounts                                                           |
| <b>Width W (Imperial)</b>                      | 1.5                                                              |
| <b>Width W (Metric)</b>                        | 38.1                                                             |
| <b>Bundle Diameter Max (Imperial)</b>          | 1.0                                                              |
| <b>Bundle Diameter Max (Metric)</b>            | 25.9                                                             |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.50                                                             |
| <b>Mounting Hole Diameter D (Metric)</b>       | 12.7 mm                                                          |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.5                                                              |
| <b>Material</b>                                | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| <b>Material Shortcut</b>                       | PA66HIRHS                                                        |
| <b>Operating Temperature</b>                   | -40°F to +257°F (-40°C to +125°C)                                |

|                                     |            |
|-------------------------------------|------------|
| <b>Reach Compliant (Article 33)</b> | Yes        |
| <b>ROHS Compliant</b>               | Yes        |
| <b>Package Quantity (Imperial)</b>  | 150        |
| <b>Package Quantity (Metric)</b>    | 150        |
| <b>Customs Number</b>               | 3926909988 |