


Specification Sheet

Part Number: 151-00992



Clip can be installed by hand – no need for hardware or tools. Design provides low insertion and high extraction force, for simple, secure performance.

Clip keeps bundle away from areas that could cause damage due to rubbing.

Standoff Bundling Clip, 1.98" Long, Panel Thickness 0.02–0.27", PA66HIRHSUV, Black, 3000/carton

Article Number	151-00992
Type	SOC11FTOVAL
Color	Black (BK)
Quantity Per	carton
Product Description	Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.
Short Description	Standoff Bundling Clip, 1.98" Long, Panel Thickness 0.02–0.27", PA66HIRHSUV, Black, 3000/carton

Global Part Name

SOC11FTOVAL-PA66HIRHSUV-BK

Length L (Imperial)

1.98

Length L (Metric)

50.2

Offset Length (Imperial)

0.79

Offset Length (Metric)

20.0

Fixation Method

Fir Tree for oval holes

Height H (Imperial)

0.79

Height H (Metric)

20.1

Panel Thickness Min (Imperial)

0.023

Panel Thickness Max (Imperial)

0.27

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

6.75

Mounting Hole Diameter D (Imperial)

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

Mounting Hole Diameter D (Metric)

6.5 x 13.0 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)

0.51

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3926909988