

## Specification Sheet

Part Number: 126-00086



Dome provides a tight, rattle-free installation.  
Outside serrated strap has ribs designed for convoluted tubing.  
Dome acts as a seal to keep out dust and liquid.

1-Pc Cable Tie/Arrowhead Mount w/Disc, 6.2"L, 0.25" - 0.26" Hole Dia, PA66HS, Black, 500/pkg

**Article Number** 126-00086

**Type** T50SOSKSFT6.5S2-E

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.

**Short Description** 1-Pc Cable Tie/Arrowhead Mount w/Disc, 6.2"L, 0.25" - 0.26" Hole Dia, PA66HS, Black, 500/pkg

**Global Part Name** T50SOSKSFT6.5S2-E-PA66HS-BK

**Technical Description** Please quote and sell 126-00326

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 6.0

**Length L (Metric)** 157.5

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

**Width W (Imperial)** 0.18

**Width W (Metric)** 4.6

**Bundle Diameter Min (Imperial)** 0.04

**Bundle Diameter Min (Metric)** 1.0

**Bundle Diameter Max (Imperial)** 1.4

<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.3
<b>Height H (Imperial)</b>	0.58
<b>Height H (Metric)</b>	1.3
<b>Panel Thickness Min (Imperial)</b>	0.07
<b>Panel Thickness Max (Imperial)</b>	0.09
<b>Panel Thickness Min (Metric)</b>	1.7
<b>Panel Thickness Max (Metric)</b>	2.3
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7
<b>Disc Diameter (Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V-2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988