

## Specification Sheet

Part Number: 151-10920



2- or 4-way entry options for the Q-Tie, offering flexibility and stability  
Designed for use with 18- through 120-pound cable ties to provide stability when securing bundles.

Secures with a single screw, providing quick installation.

**Article Number** 151-10920

**Type** CTQM5

**Color** Natural (NA)

**Quantity Per** bag

**Product Description** Q-Series mounting bases are designed to work exclusively with the Q-Tie® cable tie series. This mounting component can be secured with screws. The Q-Mount allows either a two- or four-way entry for the Q-Tie, providing a quick and simple insertion into the mount. Once in place, the Q-Tie will not slip out, even in vertical mounting applications.

**Short Description** Q Tie Mount, M4 Screw, 0.83" x 0.38" x 0.26", For Q18–Q50 ties, PA66, Natural, 100/bag

**Global Part Name** CTQM5-PA66-NA

**Length L (Imperial)** 0.83

**Length L (Metric)** 21.0

**Fixation Method** Screw Mounting and Rivet

**Width W (Imperial)** 0.38

**Width W (Metric)** 9.5

**Cable Ties** Q-Ties

**Height H (Imperial)** 0.26

**Height H (Metric)** 6.7

**Cable Tie Width Max (Imperial)** 0.2

**Cable Tie Width Max (Metric)** 5.0

**Mounting Hole Diameter D (Imperial)** 0.175

**Mounting Hole Diameter D (Metric)** 4.5 mm

**Mounting Hole Diameter D Min (Imperial)** 0.18

**Mounting Hole Diameter D Max (Metric)** 4.5

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL   ANSI/UL 746B UL   ANSI/UL 1565 UL   ANSI/UL 62275
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988

