
HellermannTyton

Specification Sheet


Part Number: 170-03180



Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.

Color options available to provide easy visual and safety identification of critical wiring components.

Expands to 150% of nominal diameter for fast, easy installation.



Braided Sleeving, Expandable, Splice Free, 0.25" Dia, PET, Black, 1000 ft/bulk reel

Article Number 170-03180

Type BSP140BSF

Color Black (BK)

Quantity Per reel

Product Description

Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation. Commonly used in electrical and industrial wire harnessing application where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.

Short Description	Braided Sleeving, Expandable, Splice Free, 0.25" Dia, PET, Black, 1000 ft/bulk reel
Global Part Name	BSP140BSF-PET-BK
Length L (Imperial)	1000.0
Bundle Diameter Min (Imperial)	0.125
Bundle Diameter Min (Metric)	3.2
Bundle Diameter Max (Imperial)	0.437
Bundle Diameter Max (Metric)	11.1
Diameter D (Imperial)	0.437
Diameter D (Metric)	10.9
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.35
Material	Polyester (PET)

Flammability FAR 25 FMVSS 302 UL 94 V-0

PET

Material Shortcut

Halogen Free Yes

Operating Temperature -94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 304.80

Customs Number 5808100000

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions