

## Specification Sheet

Part Number: 151-00663



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Bundling Clip with Fir Tree, 1.5" Long, 0.7 - 5.7mm Panel Thickness, PA66HIRHSUV, Black, 10000/box

**Article Number** 151-00663

**Type** TC6FT6

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.

**Short Description** Bundling Clip with Fir Tree, 1.5" Long, 0.7 - 5.7mm Panel Thickness, PA66HIRHSUV, Black, 10000/box

**Global Part Name** TC6FT6-PA66HIRHSUV-BK

<b>Length L (Imperial)</b>	1.5
<b>Length L (Metric)</b>	38.1
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.0
<b>Height H (Imperial)</b>	.50
<b>Height H (Metric)</b>	14.0
<b>Panel Thickness Min (Imperial)</b>	0.03
<b>Panel Thickness Max (Imperial)</b>	0.71
<b>Panel Thickness Min (Metric)</b>	0.70
<b>Panel Thickness Max (Metric)</b>	5.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.2 - 6.8 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.27
<b>Mounting Hole Diameter D Max (Metric)</b>	6.2

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	10000
<b>Package Quantity (Metric)</b>	10000
<b>Customs Number</b>	3926909988