

Specification Sheet

Part Number: 151-00018



Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Extended fir tree allows for a wide range of panel thicknesses.

Fir tree design provides low insertion forces and high extraction forces.

Convoluted Tubing Clip, 0.4" Max Bundle Diameter, Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Article Number

151-00018

Type

CTC10FT6LG

Color

Black (BK)

Quantity Per

bag

Product Description

Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

Short Description

Convoluted Tubing Clip, 0.4" Max Bundle Diameter, Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Global Part Name

CTC10FT6LG-PA66HIRHS-BK

Fixation Method

Fir Tree

Variant

Clips

Width W (Imperial)

0.31

Width W (Metric)

8.0

Height H (Imperial)

0.85

Height H (Metric)

21.4

Nominal Diameter (Imperial)

0.38

Nominal Diameter (Metric)

10.0

Panel Thickness Min (Imperial)

0.03

Panel Thickness Max (Imperial)

0.24

Panel Thickness Min (Metric)

0.75

Panel Thickness Max (Metric)

6.0

Mounting Hole Diameter D (Imperial)

0.26 - 0.28

Mounting Hole Diameter D (Metric)

6.5 - 7.0 mm

Mounting Hole Diameter D Min (Imperial)

0.283

Mounting Hole Diameter D Max (Imperial) 0.275

Mounting Hole Diameter D Max (Metric) 7.0

Disc Diameter (Metric) 16.0

Disc Diameter (Imperial) 0.63

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

