

## Specification Sheet

Part Number: 166-90372

Conduit divider fitting used to reduce conduit run diameter sizes. Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP68 fitting has additional conduit seal for increased protection against wind, dirt and water.



HelaGuard Non-Metallic IP68 Fitting, Y-Divider, 3/4" reduce to 1/2", 0.75" Dia, PA66, Black, 3/pkg

**Article Number** 166-90372

**Type** HGL075-Y050

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HelaGuard Non-Metallic Y-Divider connectors are used to reduce diameter of conduit runs and re-direct in side-by-side direction. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with small screwdriver. IP68 ingress protection rated fittings. IP68 ingress protection rated fittings.

<b>Short Description</b>	HelaGuard Non-Metallic IP68 Fitting, Y-Divider, 3/4" reduce to 1/2", 0.75" Dia, PA66, Black, 3/pkg
<b>Global Part Name</b>	HGL075-Y050-PA66-BK
<b>Variant</b>	Y-Connector
<b>Nominal Diameter (Imperial)</b>	0.38
<b>Nominal Diameter (Metric)</b>	16
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-58°F to +275°F (-50°C to +135°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes

<b>Package Quantity (Imperial)</b>	3
<b>Package Quantity (Metric)</b>	3
<b>Customs Number</b>	3926909988