

Specification Sheet

Part Number: 156-00873



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Cable tie is outside serrated to reduce bundle chafing.

Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC20, 3 - 6 mm Panel, 50lb, PA66HS, Black, 500/pkg

Article Number	156-00873
----------------	-----------

Type	T50ROSEC20
------	------------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.
---------------------	--

Short Description	Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC20, 3 - 6 mm Panel, 50lb, PA66HS, Black, 500/pkg
-------------------	---

Global Part Name	T50ROSEC20-PA66HS/PA66HIRHS-BK
-------------------------	--------------------------------

Minimum Tensile Strength (Imperial)	50.0
--	------

Minimum Tensile Strength (Metric)	225
--	-----

Length L (Imperial)	8.0
----------------------------	-----

Length L (Metric)	200.0
--------------------------	-------

Fixation Method	EdgeClip, top, assembled, 2 piece
------------------------	-----------------------------------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Variant	Outside Serrated
----------------	------------------

Width W (Imperial)	0.18
---------------------------	------

Width W (Metric)	4.6
-------------------------	-----

Bundle Diameter Min (Imperial)	0.06
---------------------------------------	------

Bundle Diameter Min (Metric)	1.5
-------------------------------------	-----

Bundle Diameter Max (Imperial)	1.77
---------------------------------------	------

Bundle Diameter Max (Metric)	45.0
-------------------------------------	------

Thickness T (Imperial)	0.05
-------------------------------	------

Thickness T (Metric)	1.3
Height H (Imperial)	0.05
Height H (Metric)	1.3
Panel Thickness Min (Imperial)	0.12
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	3.0
Panel Thickness Max (Metric)	6.0
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500

Package Quantity (Metric)	500
----------------------------------	-----

Customs Number	3926909988
-----------------------	------------