

Specification Sheet

Part Number: 170-03066



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel

Article Number 170-03066

Type BSPFR1128

Color Gray (GY)

Quantity Per reel

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel

Global Part Name BSPFR1128-PET-GY

Length L (Imperial) 40.0

Length L (Metric) 12.2

Bundle Diameter Min (Imperial) 1.0

Bundle Diameter Min (Metric) 25.4

Bundle Diameter Max (Imperial) 2.125

Bundle Diameter Max (Metric) 53.9

Diameter D (Imperial) 1.50

Diameter D (Metric) 38.1

Nominal Diameter (Imperial) 1.5

Nominal Diameter (Metric) 38.1

Material Polyester (PET)

Material Shortcut PET

Flammability FAR 25 Mil-202 FMVSS 302 UL VW-1

Halogen Free Yes

Operating Temperature -94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL 94 VW-1

UL Recognized (US) Yes

Package Quantity (Imperial) 40

Package Quantity (Metric) 12.19

Customs Number 5808100000