

## Specification Sheet

Part Number: 111-01935



Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.

**Article Number** 111-01935

**Type** T18R

**Color** Violet (VT)

**Quantity Per** bag

**Product Description** T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Purple, 100/pkg

<b>Global Part Name</b>	T18R-PA66-VT
<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80.0
<b>Length L (Imperial)</b>	3.94
<b>Length L (Metric)</b>	101.6
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1
<b>Width W (Metric)</b>	2.45
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	0.87
<b>Bundle Diameter Max (Metric)</b>	22.0
<b>Thickness T (Metric)</b>	1.0

<b>Height H (Metric)</b>	3.7
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988