

Specification Sheet

Part Number: 170-03208



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Article Number 170-03208

Type BSPFR340

Color Black (BK)

Quantity Per box

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description Braided Sleeving, Expandable, Flame Retardant, 0.75" Dia, PET, Black, 1300 ft/reel

Global Part Name BSPFR340-PET-BK

Length L (Imperial) 1300.0

Length L (Metric) 396.24

Bundle Diameter Min (Imperial) 0.5

Bundle Diameter Min (Metric) 12.7

Bundle Diameter Max (Imperial) 1.25

Bundle Diameter Max (Metric) 31.75

Diameter D (Imperial) 0.75

Diameter D (Metric) 19.05

Nominal Diameter (Imperial) 0.75

Nominal Diameter (Metric) 19.05

Material Polyester (PET)

Material Shortcut PET

Flammability FMVSS 302 FAR 25 Mil-202 UL VW-1

Halogen Free Yes

Operating Temperature -94°F to +248°F (-70°C to +120°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 1300

Package Quantity (Metric) 396.24

Customs Number 5808100000