



- NOTES
- 1 USE A P.C.B WHOSE SURFACES ARE TREATED WITH SOLDER RESIST.
 - 2 SHOW PCB LAYOUT FROM THE CONNECTOR-MOUNTING SURFACE SIDE.
 - 3 NUMBER THE CONTACTS IN THE PCB OR CONNECTOR CONSECUTIVELY FROM THE BSC SIDE.
 - 4 WHEN SCREWING THE CONNECTOR TO THE PCB, USE M2 SCREW, NUT AND WASHERS.
 - 5 HOUSING MATERIAL: CLASS 20 * FILLED PBT RESIN (W194-W), COLOR: BLACK
 - 6 CONTACT MATERIAL: PHOSPHOR BRONZE
 - 7 FINISH: NICKEL 1.27 μ MIN THK OVERALL SELECTIVE GOLD 0.06 μ MIN THK ON CONTACT AREA AND TIN-LED 1 μ MIN THK ON TINE AREA

P/N	POS	N	A	B	C	D
6-896	47	5969	6566	6966	7366	
6-648	23	2921	3518	3918	4318	
6-534	16	2032	2629	3029	3429	
6-460	29	3683	4280	4680	5080	
6-350	24	3049	3645	4045	4445	
6-240	19	2413	3010	3410	3810	
6-173280-1	30	14	1778	2375	2775	3175

AMMP ELECTRONIC TOKYO, JAPAN

CAP ASSEMBLY VERTICAL
FOR AMP-LITE 050-SERIES I-B-T-B CONV.

REV.	REV.	REV.	SHEET
5	4	3	3 OF 3

REV.	REV.	REV.	DATE	CHK.	DATE
5	4	3	1.0.84		

REV.	REV.	REV.	DATE	CHK.	DATE
5	4	3	1.0.84		

CUSTOMER DRAWING 参考面