



## 30W Interchangeable Plug Series PSC30R Adapter Series Meets CEC and EISA Requirements



### Features

- Limited Power Source
- Level IV Efficiency Compliance
- Class II Double Insulated
- Class B EMI

### Applications

- Peripherals
- Gaming Machines
- Point of Sale Equipment
- Network Equipment

### Safety Approvals

- cUL/UL
- SAA
- C-Tick

### Mechanical Characteristics

- Length: 100mm (3.9in)
- Width: 63mm (2.5in)
- Height: 36mm (1.4in)
- Weight: 260g (9oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple <sup>(1)</sup> P-P (max.)	Regulation		Efficiency Level <sup>(2)</sup>
		Min.	Max.		Line	Load	
PSC30R-120	12V	0A	2.50A	120mV	±1%	±5%	IV
PSC30R-180	18V	0A	1.67A	180mV	±1%	±5%	IV
PSC30R-240	24V	0A	1.25A	240mV	±1%	±5%	IV

(1) Measured with by-pass capacitors 0.1uF/10uF at output connector terminal.

(2) Level IV efficient products do not qualify for CE marking and therefore cannot be sold to countries in the EU

-- Interchangeable clips sold separately

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Rating**

100 to 240V AC

**AC Input Voltage Range**

90 to 264V AC

**AC Input Frequency**

47 to 63Hz

**Input Current**

0.8A (RMS) maximum at 120V AC

0.5A (RMS) maximum at 240V AC

**Leakage Current**

0.25mA maximum

**Inrush Current**

<30A for 120V AC at maximum load

<60A for 240V AC at maximum load

(Cold start at ambient 25°C)

**Input Power Saving**

0.5W maximum at no load

**Output:**

**Efficiency**

>80.6% average efficiency

**Environmental:**

**Temperature**

Operation 0 to +40°C

Non-operation -25 to +85°C

Humidity 20 to 90%

**Emissions**

FCC Class B

EN55022 Class B

**Immunity**

IEC61000-4-2

IEC61000-4-3

IEC61000-4-4

IEC61000-4-5

IEC61000-4-6

IEC61000-4-11

EN61000-3-2

**Over-Voltage Protection**

120% by zener clamping

**Over-Current Protection**

Short circuit protection – auto-restart

**Short-Circuit Protection**

Output can be shorted without damage

**Dielectric Withstand (Hi-pot) Test**

Primary to Secondary: 3000V AC for 1 min., 10mA

**DC Output Connector**

2.1 x 5.5mm Center Positive Standard

**AC Input Clips (sold separately)**

RPA: US

RPI: India

RPB: Brazil

RPK: UK

RPC: China

RPN: Argentina

RPE: Europe

RPS: Australia

RPH: Korea

RPX: IEC320 C8

**Dimension Diagram Unit: mm (inch)**

