


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00431	Connector, USB B mini receptacle	1	
2	50-00432	Connector, USB A mini male	1	
3	30-00099	Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 3.6mm, shielded, VW-1, PVC, 79A, USB 2.0, white	1	
4	24-00060	Overmold, jack, USB mini B	1	PVC, white
5	24-00022	Overmold, plug, USB mini A	1	PVC, white



Wiring diagram		
50-00431	Wire Color	50-00432
1	Red	1
2	White	2
3	Green	3
5	Black	4 & 5
Shell	Drain & Shield	Shell

**Notes:**

Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>				
A	9/21/2011	Initial release	Verified:			RoHS compliant			
A1	1/29/2014	Corrected shield type	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	<table border="1"> <tr> <td>Size:</td> <td>Part number:</td> </tr> <tr> <td>A</td> <td>10-00784</td> </tr> </table>	Size:	Part number:	A	10-00784
Size:	Part number:								
A	10-00784								
A2	11/1/2018	Removed label	Description:	Cable, 100 mm, USB mini B 5P receptacle to USB mini A male, 28 AWG, 30-00099 wire, white	<table border="1"> <tr> <td>Scale:</td> <td>1:1</td> <td></td> <td>Sheet 1 of 1</td> </tr> </table>	Scale:	1:1		Sheet 1 of 1
Scale:	1:1		Sheet 1 of 1						

5

4

3

2

1