

Specification Sheet

Part Number: 166-90466

External NPT thread provides a secure connection.

Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.

Elbow features a smooth, swept bore to ease cable installation.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP66 fitting has one-piece construction.



HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 2" NPT Thread, 2" Dia, PA66, Black, 2/pkg

Article Number 166-90466

Type HG200-90-2000

Color Black (BK)

Quantity Per pack

Product Description HelaGuard Non-Metallic 90-Degree Elbow fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

Short Description	HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 2" NPT Thread, 2" Dia, PA66, Black, 2/pkg
Global Part Name	HG200-90-2000-PA66-BK
Variant	90° Elbow
Nominal Diameter (Imperial)	2.63
Nominal Diameter (Metric)	67
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-58°F to +275°F (-50°C to +135°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity (Imperial)	2
Package Quantity (Metric)	2
Customs Number	3926909988