



## Screw Terminal Blocks

### 2000/12 DS

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 16.0 mm<sup>2</sup>, pin spacing: 14.50 mm, mounting hole diameter: 4.3 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 76.0 A



### Order Info

|                             |               |
|-----------------------------|---------------|
| reference number (ref. no.) | 128312        |
| PU                          | 20            |
| EAN                         | 4028012106585 |

### Type

|                         |                      |
|-------------------------|----------------------|
| type                    | terminal block       |
| number of poles         | 12 pole              |
| clamping units per pole | 1                    |
| colour                  | natural              |
| cross-section rating    | 16.0 mm <sup>2</sup> |
| connection type         | screw                |
| wire protector (DS)     | yes                  |

### Technical Data

|                                    |                      |
|------------------------------------|----------------------|
| voltage rating                     | 500 V                |
| current rating                     | 76.0 A               |
| insulating material                | PA 6                 |
| contact material                   | brass                |
| core cross-section min.            | 0.5 mm <sup>2</sup>  |
| core cross-section max.            | 10.0 mm <sup>2</sup> |
| flammability rating                | V-2                  |
| min. Umgebungstemperatur           | -40 °C               |
| max. Ambient Temperature Operation | 85 °C                |
| type of conductor solid            | yes                  |
| type of conductor flexible         | yes                  |
| type of conductor stranded         | yes                  |
| stripping length                   | 10.0-10.5 mm         |
| Assembly Contact Screw             | 1.0x5.5 / ⌀ 2.0 Nm   |
| mounting hole diameter             | 4.3 mm               |
| pin spacing                        | 14.50 mm             |
| fixing                             | screw                |

## Approvals

|                         |                              |
|-------------------------|------------------------------|
| <b>acc. to EN 60998</b> | <a href="#">Download PDF</a> |
| <b>acc. to UL</b>       | <a href="#">Download PDF</a> |
| <b>acc. to CSA</b>      | <a href="#">Download PDF</a> |

## Accessories

|                |        |
|----------------|--------|
| <b>ZEL 110</b> | 196420 |
|----------------|--------|