# **Heat Shrink Heavy Duty Breakout Boot, 3-Way Outlet**


## 3M Part Numbers HDBB-310 to 345


## **Typical Applications**

These breakout boots provide strain relief and environmental/mechanical protection for breakouts in multiconductor armored or sheathed cables. This style is designed for three breakouts.

#### **Expanded part (as supplied)**

## Fully recovered part (after heating)





|                | NAVSEA or                         | Cable End<br>H DIA |         | Conductor Legs<br>J DIA |         | P<br>±10%<br>R | R<br>±10%<br>R | HW<br><u>+</u> 20%<br>R |
|----------------|-----------------------------------|--------------------|---------|-------------------------|---------|----------------|----------------|-------------------------|
| PART NUMBER    | DOD-STD-<br>2003-1 Part<br>Number | MIN X              | MAX R   | MIN X                   | MAX R   |                |                |                         |
| HDBB-310-1-250 | 1A62-5                            | 0.90               | 0.36    | 0.33                    | 0.12    | 2.70           | 0.70           | 0.10                    |
|                |                                   | (22.86)            | (9.14)  | (8.38)                  | (3.05)  | (68.58)        | (17.78)        | (2.54)                  |
| HDBB-320-1-250 | 1A62-6                            | 1.20               | 0.50    | 0.50                    | 0.16    | 3.30           | 1.00           | 0.10                    |
|                |                                   | (30.48)            | (12.70) | (12.70)                 | (4.06)  | (83.82)        | (25.40)        | (2.54)                  |
| HDBB-321-1-250 | 1A62-7                            | 1.50               | 0.69    | 0.65                    | 0.18    | 4.00           | 2.20           | 0.90                    |
|                |                                   | (38.10)            | (17.53) | (16.51)                 | (4.57)  | (101.60)       | (55.88)        | (22.86)                 |
| HDBB-325-1-250 | 1A62-8                            | 1.70               | 0.90    | 0.82                    | 0.30    | 4.50           | 1.20           | 0.14                    |
|                |                                   | (43.18)            | (22.86) | (20.83)                 | (7.62)  | (114.30)       | (30.48)        | (3.56)                  |
| HDBB-335-1-250 | 1A62-9                            | 2.40               | 1.40    | 1.25                    | 0.50    | 5.10           | 1.60           | 0.15                    |
|                |                                   | (60.96)            | (35.56) | (31.75)                 | (12.70) | (129.54)       | (40.64)        | (3.81)                  |
| HDBB-340-1-250 | 1A62-10                           | 3.20               | 2.00    | 1.40                    | 0.75    | 5.10           | 1.60           | 0.15                    |
|                |                                   | (81.28)            | (50.80) | (35.56)                 | (19.05) | (129.54)       | (40.64)        | (3.81)                  |
| HDBB-345-1-250 | 1A62-11                           | 4.90               | 2.32    | 2.00                    | 1.00    | 10.00          | 2.50           | 0.13                    |
|                |                                   | (124.46)           | (58.93) | (50.80)                 | (25.40) | (254.00)       | (63.50)        | (3.30)                  |

- · All dimensions in both inches and metric, all angles in degrees
- Dimensions in table: X = Expanded (Minimum) R = Recovered (Maximum)
- · Color: Black
- 3M CAGE Code: 20999

#### **Materials Available**

- Semi-rigid Flame Retardant Polyolefin
- -3 Flexible Polyolefin, Halogen Free
- Flexible Flame Retardant Polyolefin

Description Thermoplastic 80°C

## **Important Notice**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.

