Part Number: 1202540120
Status: Active
Overview: Contrinex Inductive and Photoelectric Sensors
Description: Contrinex Photoelectric Sensor, M18 Plastic Housing, Through-Beam (Receiver), 0 - 30000mm Operating Distance, PNP, Changeover/IOL, 4-pin M12 Connector, 37mm Housing Length



Series image - Reference only

Documents:
Product Specification 1202540120-000 (PDF)
RoHS Certificate of Compliance (PDF)
Datasheet (PDF)

EU ELV
Not Relevant

EU RoHS | **China RoHS**
Compliant

REACH SVHC
Not Reviewed

Halogen-Free Status
Not Reviewed

For more information, please visit Contact US

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
120254 Series

General	
Product Family	Sensors
Series	120254
IP Rating	IP67
Operating Principle	Through-Beam (Receiver)
Overview	Contrinex Inductive and Photoelectric Sensors
Product Category	Photoelectric Sensors
Product Name	Contrinex
Type	Photoelectric
UPC	191130068562
Physical	
Connection	Connector (M12, 4-pin)
Length	37mm
Material - Housing	ABS
Material - Window	PMMA
Net Weight	87.000/g
Operating Distance	0 - 30000mm
Output	Changeover/IOL
Sensor Housing Size	M18
Temperature Range - Operating	-25° to +55°C
Electrical	
Polarity	PNP
Switching Frequency	≤ 1000 Hz
Material Info	
Engineering Number	LLR-M18PA-NMS-603
Reference - Drawing Numbers	
Product Specification	1202540120-000