

902-928 MHz FORKLIFT MOUNT 6dBic CP RFID PANEL ANTENNA

The Laird Technologies' S9026X antenna gives RFID users an antenna that meets all of the criteria requirements for forklift RFID applications. At only 7.6" x 7.6" x .95", the antenna is small enough to accommodate a wide variety of forklift applications. The antenna provides 6dBi of gain in the 902-928 MHz band.

The antenna material construction is unique in that it is an all metal antenna. No exterior radome enclosure is required to protect critical components. The result is an antenna that is extremely robust and resistant to damage.

The antenna can be mounted directly to the forklift allowing for a view directly into any pallet. Two antennas can be mounted side by side on a custom configured mounting platform if that is desirable.

The antenna is provided with a plastic front panel that is secured with adhesive for the purposes of providing a surface that can be used for branding or for any other graphical element that the customer might desire.

FEATURES

- Low profile
- Extremely low VSWR
- Wide band
- Weather resistant radome
- Wide range of connector and cable options

APPLICATIONS

- Direct forklift mount
- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyor belt


global solutions: local support.™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com


Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Right-hand circularly polarized linear azimuth plot



Right-hand circularly polarized linear elevation plot

SPECIFICATIONS

Antenna Part Number	S9026XRRN
Frequency Range	902 - 928 MHz
Gain	6 dBic
Maximum VSWR	1.5:1
3 dB Beamwidth - Azimuth	80°
Front to Back Ratio	10 dB
Polarization	Circular Right-hand
Maximum Input Power	4 Watts
Input Impedance	50 Ohms
Axial Ratio	3 dB
Weight (Kg)	2.6 lbs (1.2)
Mechanical Size	7.59" x 7.59" x .95"
Antenna Connection	Right Angle Type N Female
Radome	Aluminum w/ Minimal Polycarbonate
Mount Style	Chassis mount
Temperature Operational	-30°C to +70°C
Lightning Protection	DC Grounded

ANT-DS-S9026X 0310

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.