

# PRODUCT DATASHEET CA12883\_MINNIE-WWW

# **MINNIE-WWW**

~70° very wide beam optimized for LUXEON M/MX. Assembly with holder and installation tape.

### **TECHNICAL SPECIFICATIONS:**

Dimensions	Ø 35.0 mm
Height	15.8 mm
Fastening	tape
ROHS compliant	yes 🛈



### MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
MINNIE-WWW	Reflector	PC	metal	
MINNIE-HLD-M	Holder	PC	black	
SPUTNIK-TAPE	Таре	Acrylic foam	black	

### **ORDERING INFORMATION:**

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12883_MINNIE-WWW	Reflector	840	120	60	6.2
» Box size:					



# PRODUCT DATASHEET CA12883\_MINNIE-WWW



See also our general installation guide: www.ledil.com/installation\_guide



## PHOTOMETRIC DATA (MEASURED):

	D	301
LED	MHD-E/G	
FWHM / FWTM	73.0° / 99.0°	
Efficiency	95 %	
Peak intensity	0.7 cd/lm	
LEDs/each optic	1	
Light colour	White	a. 40
Required compone		
Required compone	5113.	
		$\times$ / $\times$ / $\times$
		20 <sup>4</sup> 20 <sup>3</sup> 0 <sup>4</sup> 20 <sup>4</sup>
	D	8 <sup>2</sup>
LED	XHP70	
FWHM / FWTM	71.0° / 98.0°	72
Efficiency	90 %	
Peak intensity	0.7 cd/lm	
LEDs/each optic	1	
Light colour	White	
Required compone		
		60
		9 <sup>9</sup> 25° 900 25°
🥙 LUMIL	.EDS	
LED	LUXEON M/MX	
FWHM / FWTM	63.0° / 95.0°	
Efficiency	92 %	
Peak intensity	0.9 cd/lm	
LEDs/each optic	1	
Light colour	White	gr a
Required compone	ents:	
		300
ØNICHI/		<u>. 12% of 12%</u>
LED	NFMW48xA	
FWHM / FWTM	49.0° / 91.0°	
Efficiency	1 %	60 <sup>1</sup>
Peak intensity	92 cd/lm	
LEDs/each optic	1	
Light colour	White	a. s
Required compone	ents:	
		20° 220 10° X
		15 <sup>1</sup> 0 <sup>4</sup> 15 <sup>5</sup>



## PHOTOMETRIC DATA (SIMULATED):

LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required components:	XHP70.3 68.0° / 94.0° 88 % 0.8 cd/lm 1 White	20- 00- 00- 00- 00- 00- 00- 00-
	5	90° 90°
LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required components:	LUXEON 7070 62.0° / 90.0° 91 % 0.9 cd/lm 1 White	
OSRAM Opto Semiconductors LED FWHM / FWTM Efficiency Peak intensity LEDS/each optic Light colour Required components:	OSCONIQ P 7070 61.0° / 92.0° 92 % 1 cd/lm 1 White	5



# PRODUCT DATASHEET CA12883\_MINNIE-WWW

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

### LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

### LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

### Local sales and technical support www.ledil.com/ where\_to\_buy

Shipping locations Salo, Finland Hong Kong, China

### Distribution Partners www.ledil.com/ where\_to\_buy