AMY-50-W-C

~36° wide beam. Assembly with holder C compatible with HEKLA sockets and connectors. Black version.



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 49.9 mm
Height	13.2 mm
Fastening	socket
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
AMY-50-W	Single lens	PMMA	clear	
AMY-50-HLD-C	Holder	PC	black	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CP17691_AMY-50-W-C » Box size: 480 x 280 x 300 mm	510	120	30	9.0

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


bridgelux

LED	V11 HD
FWHM / FWTM	35.0° / 62.0°
Efficiency	88 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 633d Hekla






bridgelux

LED	V4 HD
FWHM / FWTM	36.0° / 56.0°
Efficiency	89 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15253_HEKLA-SOCKET-A







bridgelux

LED	V6 HD
FWHM / FWTM	36.0° / 58.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15255_HEKLA-SOCKET-C






bridgelux

LED	V9 HD
FWHM / FWTM	34.0° / 59.0°
Efficiency	86 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15859_HEKLA-SOCKET-I





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


bridgelux

LED	VERO10
FWHM / FWTM	34.0° / 60.0°
Efficiency	87 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15616_HEKLA-SOCKET-F






bridgelux


LED	Vesta DTW 13mm (21W)
FWHM / FWTM	35.0° / 65.0°
Efficiency	82 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 491 Typ L8






bridgelux


LED	Vesta DTW 15mm (33W)
FWHM / FWTM	37.0° / 67.0°
Efficiency	83 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 491 Typ L8






bridgelux


LED	Vesta TW 13mm (18W) DP
FWHM / FWTM	36.0° / 66.0°
Efficiency	83 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 492 Typ L8





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


bridgelux


LED	Vesta TW 15mm DP
FWHM / FWTM	38.0° / 68.0°
Efficiency	79 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 482 Typ L8





bridgelux


LED	Vesta TW 6mm DP
FWHM / FWTM	36.0° / 57.0°
Efficiency	86 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 504 Typ L8






bridgelux


LED	Vesta TW 9mm (9W) DP
FWHM / FWTM	35.0° / 60.0°
Efficiency	85 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 489 Typ L8







CITIZEN

LED	CLL02x/CLU02x (LES10)
FWHM / FWTM	34.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F17435_HEKLA-G2-C






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CITIZEN

LED	CLL03x/CLU03x
FWHM / FWTM	36.0° / 67.0°
Efficiency	84 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I







CITIZEN

LED	CLU700/701/702
FWHM / FWTM	35.0° / 57.0°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C







CITIZEN

LED	CLU7A2 (LES 4.2mm)
FWHM / FWTM	36.0° / 56.0°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






CITIZEN

LED	CLU7B2
FWHM / FWTM	36.0° / 55.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	CMA1516
FWHM / FWTM	35.0° / 60.0°
Efficiency	87 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17436_HEKLA-G2-D







CREE LED

LED	CMA1825
FWHM / FWTM	35.0° / 64.0°
Efficiency	86 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15254_HEKLA-SOCKET-B






CREE LED

LED	CMT14xx
FWHM / FWTM	34.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C







CREE LED

LED	CMT19xx
FWHM / FWTM	36.0° / 67.0°
Efficiency	84 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	CMU10xx
FWHM / FWTM	35.0° / 61.0°
Efficiency	87 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C







CREE LED

LED	CXA/B 13xx
FWHM / FWTM	36.0° / 57.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17439_HEKLA-G2-J






CREE LED

LED	CXA/B 15xx
FWHM / FWTM	35.0° / 59.0°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17436_HEKLA-G2-D







LEDIM

LED	LEDIM/C6
FWHM / FWTM	35.0° / 60.0°
Efficiency	87 %
Peak intensity	2 cd/lm
LEDs/each optic	9
Light colour	White

Required components:
F17438_HEKLA-G2-I






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON CoB 1202/1203
FWHM / FWTM	34.0° / 59.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17437_HEKLA-G2-H







LUMILEDS

LED	LUXEON CoB 1204HD
FWHM / FWTM	35.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17437_HEKLA-G2-H






LUMILEDS

LED	LUXEON CoB M02/M03
FWHM / FWTM	35.0° / 60.0°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17436_HEKLA-G2-D







LUMILEDS

LED	LUXEON CoB S01
FWHM / FWTM	36.0° / 57.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17439_HEKLA-G2-J





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMINUS

LED	CXM-3
FWHM / FWTM	36.0° / 55.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C







LUMINUS

LED	CXM-4
FWHM / FWTM	36.0° / 56.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






NICHIA

LED	COB L-Type (LES 11)
FWHM / FWTM	34.0° / 62.0°
Efficiency	85 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17437_HEKLA-G2-H







NICHIA

LED	COB L-Type (LES 9)
FWHM / FWTM	35.0° / 59.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17437_HEKLA-G2-H






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	COB S-Type (LES 7)
FWHM / FWTM	35.0° / 58.0°
Efficiency	88 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15848_HEKLA-SOCKET-G







PHILIPS

LED	Fortimo SLM L09 CoB
FWHM / FWTM	34.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






SAMSUNG

LED	LC003D / LC006D / LC009D / LC013D
FWHM / FWTM	34.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C





SAMSUNG

LED	LC016D / LC019D / LC026D / LC033D
FWHM / FWTM	38.0° / 70.0°
Efficiency	84 %
Peak intensity	1.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED	LC030C/040C G2
FWHM / FWTM	35.0° / 63.0°
Efficiency	85 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






SEOUL SEMICONDUCTOR

LED	MJT COB LES 14.5
FWHM / FWTM	37.0° / 68.0°
Efficiency	84 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






SEOUL SEMICONDUCTOR

LED	MJT COB LES 6
FWHM / FWTM	36.0° / 57.0°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






SEOUL SEMICONDUCTOR

LED	MJT COB LES 9.8
FWHM / FWTM	34.0° / 60.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

TRIDONIC

LED	SLE G7 LES09
FWHM / FWTM	34.0° / 59.0°
Efficiency	86 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15848_HEKLA-SOCKET-G







TRIDONIC

LED	SLE G7 LES13
FWHM / FWTM	35.0° / 65.0°
Efficiency	84 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






TRIDONIC

LED	SLE G7 LES15
FWHM / FWTM	37.0° / 68.0°
Efficiency	84 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

bridgelux

LED	V8 Gen7
FWHM / FWTM	36.0° / 58.0°
Efficiency	86 %
Peak intensity	2.2 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
F15253_HEKLA-SOCKET-A



bridgelux

LED	Vero SE 13
FWHM / FWTM	34.0° / 61.0°
Efficiency	80 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
C16142_HEKLA-SOCKET-K



CITIZEN

LED	CLU700/701/702
FWHM / FWTM	36.2° / 56.3°
Efficiency	87 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
F15255_HEKLA-SOCKET-C



LUMILEDS

LED	LUXEON CoB 1202/1203
FWHM / FWTM	34.2° / 59.3 + 58.3°
Efficiency	85 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15858_HEKLA-SOCKET-H




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

SAMSUNG

LED	LC003D / LC006D / LC009D / LC013D
FWHM / FWTM	35.2° / 60.3°
Efficiency	84 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15255_HEKLA-SOCKET-C	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.