
JENNY-CY-G2

~105° + 105° batwing light distribution for canopy and symmetrical tunnel lighting.



TECHNICAL SPECIFICATIONS:

Dimensions	35.0 x 35.0 mm
Height	11.5 mm
Fastening	tape
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
JENNY-CY-G2	Single lens	Silicone	clear	


ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F15382_JENNY-CY-G2 » Box size: 480 x 280 x 300 mm	1200	120	60	9.1


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




Front view



Isometric view
Scale: 1:1



Top view



Bottom view

INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	-	JENNY-CY-G2	Silicone	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

THIRD ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

DRAWING TITLE
JENNY-CY-G2

SIZE	PART NUMBER
A4	-


SCALE	WEIGHT	SHEET
1:1	7,4 g	1/1

See also our general installation guide: www.ledil.com/installation_guide

PHOTOMETRIC DATA (MEASURED):


CREE LED

LED	MK-R
FWHM / FWTM	105.0° / 120.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	




CREE LED

LED	XHP50
FWHM / FWTM	102.0° / 118.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	




CREE LED

LED	XHP50.2
FWHM / FWTM	106.0° / 110.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	



CREE LED

LED	XM-L EZW
FWHM / FWTM	103.0° / 119.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED	LUXEON 5258
FWHM / FWTM	103.0° / 118.0 + 120.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS

LED	LUXEON M/MX
FWHM / FWTM	102.0° / 120.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM
Opto Semiconductors

LED	Duris S8
FWHM / FWTM	102.0° / 118.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


CREE LED

LED	MX-6
FWHM / FWTM	102.0° / 118.0°
Efficiency	93 %
LEDs/each optic	1
Light colour	White
Required components:	




CREE LED

LED	XHP50.3 HD
FWHM / FWTM	103.0 + 102.0° / 112.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




CREE LED

LED	XHP50.3 HI
FWHM / FWTM	102.0° / 110.0°
Efficiency	97 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



CREE LED

LED	XHP70.3
FWHM / FWTM	105.0° / 112.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	100.0° / 110.0°
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS


LED	LUXEON 7070
FWHM / FWTM	102.0° / 112.0°
Efficiency	93 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



NICHIA


LED	NCSU334A
FWHM / FWTM	96.0° / 106.0°
Efficiency	71 %
LEDs/each optic	1
Light colour	UV-C
Required components:	

The UVC LED result tolerance is ±10 %



NICHIA

LED	NVSxE21A
FWHM / FWTM	96.0° / 108.0°
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	4
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


OSRAM
Opto Semiconductors

LED	OSCONIQ P 7070
FWHM / FWTM	100.0° / 106.0°
Efficiency	93 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z8Y22
FWHM / FWTM	102.0° / 130.0 + 110.0°
Efficiency	93 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.