


# 180 Watt Medical



## Features

- 4 x 2 x 0.75 Inches Form factor
- 180 Watts with Forced Air Cooling
- Approval to EN60601 3rd Edition
- Efficiencies upto 92%
- -40 to 70 degree operating temperature\*
- Dual fusing
- 12V / 0.5A Fan Output, Thermal Shut-Down feature
- 3.37m Hours, Telcordia -SR332-issue 3 MTBF
- No Load Power < 0.5W
- Medical (BF) Safety Approvals
- Meets standard IEC60601-1-2 : 2014 (4th Edition)

## Electrical Specifications

Input Voltage	80-264 VAC/390 VDC, Universal (Derate from 100% at 100V AC to 77% at 80V AC)	
Input Frequency	47-63 Hz	
Input Current	115 VAC: 2.2 A max.	230 VAC: 1.1 A max.
No Load Power	<0.5W typical for MULP180-1XXX and <0.85W typical for MULP180-0XXX	
Inrush Current	115 VAC – 25 A, 230 VAC – 45 A, 264 VAC – 75 A	
Leakage Current	300 uA Typical, (N.A. For Class II Option)	Touch current <100uA
Efficiency	92%(48V,58V), 90%(24V,30V), 88%(12V,15V)	
Hold-up Time	at 180W:10 ms ; 120W: 16 ms	
Power Factor	>0.95@115 VAC and 0.9@230 VAC	
Output Power	180W with 13 CFM, upto 120W Convection	
Line Regulation	+/-0.5%	
Load Regulation	+/-1%	
Transient Response	25% step load change, at 0.1A/uS slew rate, 50% duty cycle, 50Hz=4% , recovery time < 5 ms	
Rise Time	55ms typical	
Set Point Tolerance	+/-1%	
Output Voltage Adjustment	+/-3% (Ref. Note 8)	
Over Current Protection	>110%	
Over Voltage Protection	110 to 140%	
Short Circuit Protection	Hiccup mode	
Switching Frequency	PFC – 70 to 130 KHz ,PWM – 50-80 KHz	
Operating Temperature <sup>7</sup>	-40 to +70°C, * -40 to 0°C startup is guaranteed with spec deviation	
Storage Temperature	-40 to +85°C	
Relative Humidity	5% to 95%, noncondensing	
Altitude	Operating: 16,000 ft.; Nonoperating: 40,000 ft.	
MTBF	3.37m Hours, Telcordia -SR332-issue 3	
Isolation Voltage	Input to Output – 4000 VAC medical applications. Input to GND - 1500 VAC (Not Applicable For Class II Option) Output to GND- 1500VAC for type BF , 500 VAC for type B (Not Applicable For Class II Option)	
Cooling	180W with 13 CFM forced air cooling <sup>6</sup> (refer Mechanical Drawing) upto 120 W with natural convection cooling <sup>6</sup> (refer Derating Curve)	

Model Number	Type of Connector	Voltage	Max. Load (Convection) (112.5W) @50°C	Max.Load (Convection) (120W) @40°C	Max. Load (13 CFM)	Min. Load	Ripple <sup>1</sup>	Signal
MULP180-1012	Header Molex @ I/P	12 V	9.37A	10.00A	15.00A	0.0 A	2%	N.A
MULP180-1312	Screw Terminal @ O/P							
MULP180-1015	Header Molex @ I/P	12 V	9.37A	10.00A	15.00A	0.0 A	2%	N.A
MULP180-1315	Header Molex @ O/P							
MULP180-1015	Header Molex @ I/P	15 V	7.50A	8.00A	12.00A	0.0 A	2%	N.A
MULP180-1315	Screw Terminal @ O/P							
MULP180-1024	Header Molex @ I/P	15 V	7.50A	8.00A	12.00A	0.0 A	2%	N.A
MULP180-1315	Header Molex @ O/P							
MULP180-1024	Header Molex @ I/P	24 V	4.68A	5.00A	7.50A	0.0 A	1%	N.A
MULP180-1324	Screw Terminal @ O/P							
MULP180-1030	Header Molex @ I/P	24 V	4.68A	5.00A	7.50A	0.0 A	1%	N.A
MULP180-1330	Header Molex @ O/P							
MULP180-1030	Header Molex @ I/P	30 V	3.75A	4.00A	6.00A	0.0 A	1%	N.A
MULP180-1330	Screw Terminal @ O/P							
MULP180-1048	Header Molex @ I/P	30 V	3.75A	4.00A	6.00A	0.0 A	1%	N.A
MULP180-1330	Header Molex @ O/P							
MULP180-1048	Header Molex @ I/P	48 V	2.34A	2.50A	3.75A	0.0 A	1%	N.A
MULP180-1348	Screw Terminal @ O/P							
MULP180-1058	Header Molex @ I/P	48 V	2.34A	2.50A	3.75A	0.0 A	1%	N.A
MULP180-1358	Header Molex @ O/P							
MULP180-1058	Header Molex @ I/P	58 V	1.94A	2.07A	3.10A	0.0 A	1%	N.A
MULP180-1358	Screw Terminal @ O/P							
MULP180-1058	Header Molex @ I/P	58 V	1.94A	2.07A	3.10A	0.0 A	1%	N.A
MULP180-1358	Header Molex @ O/P							

ULP180-CK metal cover kit accessory

Add suffix "S1" to get model number with Input connector – Screw terminal and Output Connector – Screw Terminal. e.g. MULP180-1012-S1(Without PGPF)

Add suffix "S2" to get model number with Input connector – Right Angle Type and Output Connector – Right Angle Type. e.g. MULP180-1012-S2 (Without PGPF)




Innovations in Power

Model Number	Type of Connector	Voltage	Max. Load (Convection) (112.5W) @50°C	Max. Load (Convection) (120W) @40°C	Max. Load (13 CFM)	Min. Load	Ripple <sup>1</sup>	Signal
MULP180-0012	Header Molex @ I/P Screw Terminal @ O/P	12 V	9.37A	10.00A	15.00A	0.0 A	2%	PG & AC PF <sup>10</sup>
MULP180-0312	Header Molex @ I/P Header Molex @ O/P	12 V	9.37A	10.00A	15.00A	0.0 A	2%	PG & AC PF <sup>10</sup>
MULP180-0015	Header Molex @ I/P Screw Terminal @ O/P	15 V	7.50A	8.00A	12.00A	0.0 A	2%	PG & AC PF <sup>10</sup>
MULP180-0315	Header Molex @ I/P Header Molex @ O/P	15 V	7.50A	8.00A	12.00A	0.0 A	2%	PG & AC PF <sup>10</sup>
MULP180-0024	Header Molex @ I/P Screw Terminal @ O/P	24 V	4.68A	5.00A	7.50A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0324	Header Molex @ I/P Header Molex @ O/P	24 V	4.68A	5.00A	7.50A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0030	Header Molex @ I/P Screw Terminal @ O/P	30 V	3.75A	4.00A	6.00A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0330	Header Molex @ I/P Header Molex @ O/P	30 V	3.75A	4.00A	6.00A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0048	Header Molex @ I/P Screw Terminal @ O/P	48 V	2.34A	2.50A	3.75A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0348	Header Molex @ I/P Header Molex @ O/P	48 V	2.34A	2.50A	3.75A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0058	Header Molex @ I/P Screw Terminal @ O/P	58 V	1.94A	2.07A	3.10A	0.0 A	1%	PG & AC PF <sup>10</sup>
MULP180-0358	Header Molex @ I/P Header Molex @ O/P	58 V	1.94A	2.07A	3.10A	0.0 A	1%	PG & AC PF <sup>10</sup>
ULP180-CKP metal cover kit accessory Add suffix "S1" to get model number with Input connector – Screw terminal and Output Connector – Screw Terminal. e.g. MULP180-0012-S1(With PGPF) Add suffix "S2" to get model number with Input connector – Right Angle Type and Output Connector – Right Angle Type. e.g. MULP180-0012-S2(With PGPF)								

Connectors		
J1	Pin 1	AC LINE
	Pin 2	NOT FITTED
	Pin 3	AC NEUTRAL
J2 Option 1 & 2	Pin 1,2,3	V1 +VE
	Pin 4,5,6	V1 -VE
J3	Pin 1	FAN +VE
	Pin 2	FAN -VE
J4 (For PGPF Option Only)	Pin 1	Vs
	Pin 2	PGPF
	Pin 3	GND

## Notes

1. Ripple is peak to peak with 20 MHz bandwidth and 10  $\mu\text{F}$  (Electrolytic capacitor) in parallel with a 0.1  $\mu\text{F}$  capacitor at rated line voltage and load ranges.
2. Class II version available, Add "-II" suffix at the end of the Model Number.
3. Combined output power of main output, fan supply shall not exceed max. Power rating.
4. Fan supply output voltage tolerance including set point accuracy, line and load regulation is +/-10% and Ripple and noise is less than 10%.
5. Specifications are for nominal input voltage, 25°C unless otherwise stated.
6. 180W with 13CFM forced air cooling and 120W with natural convection cooling at 100 to 264VAC.
7. Output ripple can be more than 10% of the output voltage.
8. Adjustment potentiometer is located on the SMT side of the PCB.
9. When used in Cover Kit, de-rate output power to 70 % under all operating conditions
10. A TTL signal is available at pin 2 of J4 which goes high 100-500mS after output voltage reaches 90% of set value. It goes low a minimum of 1mS before output falls below 90% of the set value, when input AC is switched off.
11. Add suffix "S1" to get model number with Input connector – Screw terminal and Output Connector – Screw Terminal.  
e.g. MULP180-1012-S1(Without PGPF)
12. Add suffix "S2" to get model number with Input connector – Right Angle Type and Output Connector – Right Angle Type.  
e.g. MULP180-1012-S2 (Without PGPF)
13. Add suffix "S1" to get model number with Input connector – Screw terminal and Output Connector – Screw Terminal.  
e.g. MULP180-0012-S1(With PGPF)
14. Add suffix "S2" to get model number with Input connector – Right Angle Type and Output Connector – Right Angle Type.  
e.g. MULP180-0012-S2(With PGPF)



## Mechanical Specifications

AC Input Connector (J1) Option 1 (Molex Connector @ I/P)	Molex: 26-60-4030 Mating: 09-50-3031; Pins: 08-50-0106
AC Input Connector (J1) Option 2 (Screw Terminal @ I/P)	Molex: 39357 Series or equivalent
DC Output Connector (J2) Option 1 (Molex Connector @ O/P)	Molex: 26-60-4060 Mating: 09-50-3061; Pins: 08-50-0106
DC Output Connector (J2) Option 2 (Screw Terminal @ O/P)	Molex: 39357 Series or equivalent
AC Input Connector (J1) Option 3 (Right Angle Type @ I/P)	TE Connectivity: 647676-3 Mating: 1-1123722-3 ; Crimp: 1123721-2
DC Output Connector (J2) Option 3 (Molex Connector @ O/P)	TE Connectivity: 647676-6 Mating: 1-1123722-6 ; Crimp: 1123721-2
Aux (Fan) Output(J3)	AMP :640456-2 Mating: 640440-2
Signal Output (J4)	AMP :640456-3 Mating: 640440-3
Dimensions	4 x 2 x 0.75 inches (101.60 x 50.8x 19.05 mm)
Weight	200 gm approx

## EMC

Parameter	Conditions/Description	Criteria
Conducted Emissions	EN 55011-B,CISPR22-B, FCC PART15-B	Pass
Radiated Emissions	EN 55011 A	Pass (Level B with external core (King core K5B RC 25x12x15-M in input cable))
Input Current Harmonics	EN 61000-3-2	Class D
Voltage Fluctuation and Flicker	EN 61000-3-3	Pass
ESD Immunity	EN 61000-4-2	Level 4, Criterion A
Radiated Field Immunity	EN 61000-4-3	Level 3, Criterion A
Electrical Fast Transient Immunity	EN 61000-4-4	Level 3, Criterion A
Surge Immunity	EN 61000-4-5	Level 3, Criterion A
Conducted Immunity	EN 61000-4-6	Level 3, Criterion A
Magnetic Field Immunity	EN 61000-4-8	Level 4, Criterion A
Voltage dips, interruptions	EN 61000-4-11	Criterion B

## Safety


CE Mark	Complies with LVD Directive
Safety Standard(s)	EN60601-1, IEC 60601-1 (ed.3), ANSI / AAMI ES 60601 - 1, CSA C22.2 No. 60601-1
Approval Agency	Nemko, UL, C-UL
Safety File Number(s)	Class-I : UL: E173812,VOL D1, Nemko: Certificate No: P16221541, CB Test Certificate No : N094796 Class-II : UL: E173812,VOL D1, NEMKO: Certificate No: P16221548, CB Test Certificate No: N094850



Innovations in Power

## Derating Curve

### Power de-rating




Convection load: 120W UP TO 40 °C  
 De-rate between 40-50 °C @ 0.625% per °C  
 De-rate above 50 °C @ 2.33% per °C

■ Forced air  
 ■ Convection

Forced air cooled load : 180W up to 50°C  
 De-rate above 50 °C @ 2.5% per °C


### Power de-rating : w.r.t. Input





## Mechanical Drawing

Input connector – Header Molex and Output Connector – Header Molex. (Without PGPF)




MECHANICAL OUTLINE DIMENSIONS  
ALL DIMENSIONS ARE IN INCHES[MM]  
GEN TOLERANCE : +/-0.04[+/-1.0MM]

Notes: In case the PCB is mounted in a metal enclosure, using metal hardware ensure the following

1. Stand off, used to mount PCB has OD of 5.4 mm max.
2. Screws, used to fix PCB on stand off, have head dia of 6.0 mm max.
3. Washer, if used, to have dia of 6.5 mm max.

## Mechanical Drawing

Input connector – Header Molex and Output Connector – Header Molex. (With PGPF)



MECHANICAL OUTLINE DIMENSIONS  
ALL DIMENSIONS ARE IN INCHES[MM]  
GEN TOLERANCE : +/-0.04[+/-1.0MM]


Notes: In case the PCB is mounted in a metal enclosure, using metal hardware ensure the following

1. Stand off, used to mount PCB has OD of 5.4 mm max.
2. Screws, used to fix PCB on stand off, have head dia of 6.0 mm max.
3. Washer, if used, to have dia of 6.5 mm max.



## Mechanical Drawing

### Input connector – Right Angle Type and Output Connector – Right Angle (Without PGPF)



MECHANICAL OUTLINE DIMENSIONS  
ALL DIMENSIONS ARE IN INCHES[MM]  
GEN TOLERANCE :  $\pm 0.04$  [ $\pm 1.0$ MM]


MPN FOR INPUT CONNECTOR: 647676-3  
MPN FOR OUTPUT CONNECTOR: 647676-6

Notes: In case the PCB is mounted in a metal enclosure, using metal hardware ensure the following

1. Stand off, used to mount PCB has OD of 5.4 mm max.
2. Screws, used to fix PCB on stand off, have head dia of 6.0 mm max.
3. Washer, if used, to have dia of 6.5 mm max.

## Mechanical Drawing

### Input connector – Right Angle Type and Output Connector – Right Angle (With PGPF)



MECHANICAL OUTLINE DIMENSIONS  
ALL DIMENSIONS ARE IN INCHES[MM]  
GEN TOLERANCE :  $\pm 0.04$  [ $\pm 1.0$ MM]

MPN FOR INPUT CONNECTOR: 647676-3  
MPN FOR OUTPUT CONNECTOR: 647676-6

Notes: In case the PCB is mounted in a metal enclosure, using metal hardware ensure the following

1. Stand off, used to mount PCB has OD of 5.4 mm max.
2. Screws, used to fix PCB on stand off, have head dia of 6.0 mm max.
3. Washer, if used, to have dia of 6.5 mm max.