

2-Port Compact USB KVM Switch with Audio and Cable

MODEL NUMBER: **B004-VUA2-K-R**



2-port Compact USB KVM Switch with optional audio and microphone switching function allows you to access control boot and reboot two USB-enabled computers from a single keyboard monitor and mouse

Features

- Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup - no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- Compact design saves desk space
- Does not require an AC adapter
- Compatible with all major operating systems
- Includes two, 6-ft. (1.83 m) Cable Kits

Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk space
- No AC adapter required
- (x2) 6-ft. (1.83 m) USB KVM Cable kits and (x2) 6-ft. (1.83 m) 3.5mm Audio Cable kits included
- Compatible with all major operating systems

System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6-ft. (1.83 m) USB KVM Cable Kits and (2) 6-ft. (1.83 m) 3.5mm Audio Cable Kits
- CD-ROM with KVM Switcher Software
- Owner's Manual with Warranty Information

Specifications

| OVERVIEW | |
|--------------|--------------|
| UPC Code | 037332140043 |
| Product Type | KVM |



| | |
|--|---|
| Console | No |
| Max CPU | 1 |
| Technology | VGA/SVGA; Stereo Audio |
| Host Connector | (2) USB A (FEMALE) |
| VIDEO | |
| Video Input | HD15 (FEMALE) |
| Video Output | HD15 (FEMALE) |
| Number of Monitors Supported | 1 |
| Video Ports | (3) HD15 (FEMALE) |
| Max Supported Video Resolution | 2048 x 1536 @60Hz |
| AUDIO | |
| Audio Ports | (2) 3.5MM (FEMALE) |
| Audio Ports Details | Connect a microphone and speaker via the dual 3.5mm audio ports |
| Audio Input | 3.5mm |
| Audio Output | Audio |
| Audio Specification | Stereo Audio |
| DATA | |
| Data Ports | (2) USB A (FEMALE) |
| Data Ports Details | (2) USB-A - USB 2.0 |
| INPUT | |
| Bus Powered | Yes |
| Power Source | Bus; USB |
| POWER | |
| Power Consumption (Watts) | 0.5 |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Green (Selected PC) |
| PHYSICAL | |
| Material of Construction | ABS |
| Color | Black |
| Cable Jacket Color | Black |
| Total Number of Ports | 9 |



| | |
|---------------------------------------|-------------------------------|
| Shipping Dimensions (hwd / cm) | 7.62 x 20.07 x 19.81 |
| Shipping Dimensions (hwd / in.) | 3.00 x 7.90 x 7.80 |
| Shipping Weight (kg) | 0.82 |
| Shipping Weight (lbs.) | 1.80 |
| Unit Dimensions (hwd / in.) | 1.3 x 4 x 2.6 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.22 |
| Unit Weight (kg) | 0.10 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) |
| Relative Humidity | 0%-90% RH, Non-Condensing |
| BTUs | 1.7 BTU/Hr |
| ESD Protection | Yes |
| COMMUNICATIONS | |
| Hotkey | Yes |
| IP Remote Access | No |
| EDID Compatible | Yes |
| IR Remote Extension Support | No |
| CONNECTIONS | |
| Number of Ports | 2 |
| Daisy-Chain Port | No |
| Firmware Upgrade Port | No |
| PC/Server Connections | USB; VGA |
| Side A - Connector 1 | (2) HD15 (FEMALE) |
| Side B - Connector 1 | HD15 (FEMALE) |
| Side B - Connector 2 | (2) USB A (FEMALE) |
| Side B - Connector 3 | (2) 3.5MM (FEMALE) |
| Side B - Connector 4 | (2) USB MINI-B 5-PIN (FEMALE) |
| Included Cable (Side A) - Connector 1 | Yes |
| Computer Keyboard and Mouse Interface | USB |
| Computer Monitor Interface | VGA |



| | |
|--------------------------------------|-------------------------------------|
| Console Keyboard and Mouse Interface | USB |
| Console Monitor Interface | VGA |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| Autoscan (Y,N) | Y |
| Autoscan Duration | 10 - 60 seconds |
| Number of Users | 1 |
| NIAP-Certified Secure | No |
| On-Screen Display (OSD) | No |
| Port Selection | Pushbutton; Hotkey; Software |
| USB Hub Ports | Yes |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| Cat5 KVM Switch | No |
| STANDARDS & COMPLIANCE | |
| Certification & Compliance | CE (Europe); RoHS; REACH; FCC (USA) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>