



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

## Protect It! 7-Outlet Surge Protector, 6 ft. (1.83 m) Cord, 1080 Joules, Fax/Modem Protection, RJ11

MODEL NUMBER: **SUPER6TEL**



### Highlights

- 7 outlets / 6-ft. cord
- 1080 joule rating
- Modem/fax surge protection

### Package Includes

- SUPER6TEL Surge Suppressor
- 6-ft. (1.83 m) telephone cord
- Instruction manual with warranty information

### Description

Tripp Lite's SUPER6TEL surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. High-grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. SUPER6TEL offers 7 total outlets, 6 foot cord with a space-saving right angle plug and diagnostic LEDs to warn of wiring problems and suppressor damage. Heavy grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 3 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only). PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/6-ft. (1.83 m) AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Corded multi-outlet strip with 3 transformer spaced outlets SUPPRESSION: AC: 150V RMS Clamping/1080 joules/400V UL1449 Let-through Phone: Single telephone line surge suppression (RJ11 jacks, 2 wire, 1 line)

### Features

- 1080 joules AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with room for 3 transformer plugs without blocking outlets covers computers and all peripherals
- Phone line surge suppression protects both dialup and DSL modems, plus fax machines, cordless phones and more (pair of RJ11 jacks, 2 wire, 1 line, includes 6-ft. (1.83 m) phone cable)
- 6-ft. (1.83 m) cord with space-saving right-angle plug
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LEDs confirm outlet grounding and surge suppression status
- UL1449 3rd Edition Rated (400V all modes), UL1363 (Power Tap), UL497A (Communications), Meets FCC part 68 rules, cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications
- \$50,000 Ultimate Lifetime connected equipment insurance (U.S., Canada, and Puerto Rico only)



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

## Specifications

| OVERVIEW                           |                                                                      |
|------------------------------------|----------------------------------------------------------------------|
| UPC Code                           | 037332095428                                                         |
| INPUT                              |                                                                      |
| Nominal Input Voltage(s) Supported | 120V AC                                                              |
| Recommended Electrical Service     | 120V (110-125V)                                                      |
| Input Plug Features                | Right Angle                                                          |
| Input Cord Gauge Type              | 14 gauge; SJT                                                        |
| Input Cord Gauge (AWG)             | 14                                                                   |
| Voltage Compatibility (VAC)        | 120                                                                  |
| Maximum Surge Amps                 | 72000                                                                |
| Input Plug Type                    | NEMA 5-15P                                                           |
| Input Cord Details                 | SJT                                                                  |
| Input Cord Length (ft.)            | 6                                                                    |
| Right-Angle Plug                   | Yes                                                                  |
| Input Cord Length (m)              | 1.83                                                                 |
| Integrated Cord Clip               | No                                                                   |
| OUTPUT                             |                                                                      |
| Frequency Compatibility            | 50 / 60 Hz                                                           |
| Output (Watts)                     | 1800                                                                 |
| Output Receptacles                 | (7) 5-15R                                                            |
| Circuit Breaker (amps)             | 15                                                                   |
| Transformer Accommodation          | (4) Yes                                                              |
| Outlet Orientation                 | Single row of 5, plus 2 side mounted outlets                         |
| Right-Angle Outlets                | No                                                                   |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                      |
| Diagnostic LED(s)                  | Yes                                                                  |
| Switches                           | Two position on/off power switch                                     |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status |
| SURGE / NOISE SUPPRESSION          |                                                                      |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                   |                                                                                    |
|---------------------------------------------------|------------------------------------------------------------------------------------|
| AC Suppression Joule Rating                       | 1080                                                                               |
| AC Suppression Response Time                      | < 1 ns                                                                             |
| Protection Modes                                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| UL1449 Let Through Rating                         | 400V                                                                               |
| EMI / RFI Filtering                               | Up to 20 dB                                                                        |
| Automatic Shut-Off                                | No                                                                                 |
| <b>DATALINE SURGE SUPPRESSION</b>                 |                                                                                    |
| Telephone/DSL Protection Details                  | 1 line                                                                             |
| Cable (Coax) Protection                           | No                                                                                 |
| Network (Ethernet) Protection                     | No                                                                                 |
| Telephone/DSL Protection                          | Yes                                                                                |
| <b>PHYSICAL</b>                                   |                                                                                    |
| Material of Construction                          | Plastic                                                                            |
| Antimicrobial                                     | No                                                                                 |
| Power Cord Color                                  | Gray                                                                               |
| Housing Color                                     | Light Gray                                                                         |
| Mounting Holes or Slots                           | Yes                                                                                |
| Slot or Hole Mount Measurement (Center to Center) | Distance between slots = 70 mm; Distance between slot height = 24 mm               |
| Outlets Measurement (Center to Center)            | Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm                |
| Receptacle Color                                  | Gray                                                                               |
| Shipping Dimensions (hwd / cm)                    | 32.77 x 5.84 x 15.24                                                               |
| Shipping Dimensions (hwd / in.)                   | 12.90 x 2.30 x 6.00                                                                |
| Shipping Weight (kg)                              | 0.68                                                                               |
| Shipping Weight (lbs.)                            | 1.50                                                                               |
| Unit Dimensions (hwd / in.)                       | 1.54 x 2.72 x 10.3                                                                 |
| Unit Dimensions (hwd / cm)                        | 3.91 x 6.91 x 26.16                                                                |
| Unit Weight (lbs.)                                | 1.39                                                                               |
| Unit Weight (kg)                                  | 0.63                                                                               |
| Input Cord Color                                  | White                                                                              |
| <b>FEATURES &amp; SPECIFICATIONS</b>              |                                                                                    |
| Rotatable Outlets                                 | No                                                                                 |
| <b>STANDARDS &amp; COMPLIANCE</b>                 |                                                                                    |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                            |                                                                                                                       |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Canada                                                     | cUL                                                                                                                   |
| Approvals                                                  | Exceeds IEEE 587 category A&B specifications                                                                          |
| UL1449 3rd Edition (AC Suppression)                        | UL1363:2018 (5th Ed); UL1449:2014 (4th Ed), CAN/CSA-C22.2 No. 269.3:2017 (2nd Ed); CAN/CSA-C22.2 No.308-14            |
| NOM (Mexico)                                               | NOM                                                                                                                   |
| UL1363 (Power Tap)                                         | UL1363                                                                                                                |
| UL497A (Communications)                                    | UL497A                                                                                                                |
| FCC Part 68 (Communications)                               | FCC Part 68                                                                                                           |
| Industry Canada (Communications)                           | Industry Canada                                                                                                       |
| <b>WARRANTY</b>                                            |                                                                                                                       |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                             |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$50,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>