

## Slim Line Keypad G84-4700

USB version

### Numeric Keypad



### Key benefits

Cherry ML technology  
with Gold Crosspoint contacts

21 keys, thereof four individually inscribable  
function keys

Small dimensions

Ideal for right- and left-hand users

All keys programmable by software  
„Cherry-Tools“

Combo Interface (USB · PS/2)

### Approvals

WHQL (Windows Hardware Quality Lab)  
"Designed for Windows 2000 and XP"

CE, GS/ÜG, VDE, cURus, FCC DoC Cl. B,  
VCCI Cl. 2, BSMI, C-Tick, GOST-R

### System requirements

USB connection

Windows 98, ME, 2000, XP  
(for programming of keys by software)

### Delivery volume

Keypad, printed instructions,  
CDROM (software, manual)

### Technische Daten

#### Interface

USB  
PS/2 with adaptor (not included in delivery)

#### Current consumption

USB: max. 100 mA  
PS/2 (with adaptor): approx. 50 mA

#### Number of keys

21 (4 keys inscribable)

#### Operating life of individual keys

> 50 million operations

#### Cable length

approx. 1,75 m

#### Weight

approx. 185 g (without packaging)  
approx. 270 g (with packaging)

**Dimensions**

approx. 90 x 132 x 36 mm (Keypad)  
approx. 140 x 185 x 45 mm (packaging)

**Reliability**

MCBF > 10<sup>9</sup> operations  
MTBF > 100,000 hours

**Storage temperature**

-25 °C to 65 °C

**Operating temperature**

0 °C to 50 °C

**Packaging unit**

72 keypads per master carton  
576 keypads per palette

**Guarantee period**

2 years

**Order description**

<b>Order no.</b>	<b>Colour</b>	<b>Interface</b>
G84-4700LUCxx-0	light grey	USB
G84-4700PUCxx-2	black	USB

The xx in the order no. defines the country version.

BE	Belgium
CH	Switzerland
DE	Germany
DK	Denmark
ES	Spain
EU	US English/international with €
FR	France
GB	English (UK)
IT	Italy
NO	Norway
PO	Portugal
SF	Sweden / Finland
US	English (US)

Other versions upon request.

Cherry GmbH  
Cherrystraße  
D-91275 Auerbach/Opf.  
Phone: +49 9643 18-0  
Hotline: +49 9643 18-206  
Fax: +49 9643 18-1545  
Internet: [www.cherrycorp.com](http://www.cherrycorp.com)

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relate to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.