

**May not be suitable for all medical and aerospace applications.
Specifications: Contact Mallory Sonalert to discuss your application.**

NO CIRCUITRY

| | |
|--|-----------------------------------|
| Oscillation Frequency (Hz) | 2048 |
| Operating Voltage (Vp-p) | 1.25 ~ 2.5 |
| Rated Voltage (Vp-p) | 1.5 |
| Current Consumption Max. (mA) | 32 at Rated Voltage |
| Sound Pressure Level Min. (dB) | 85 at 10cm at Rated Voltage |
| Coil Resistance (Ω) | 16 ± 2 |
| Operating Temperature ($^{\circ}\text{C}$) | $-20 \sim +70$ |
| Storage Temperature ($^{\circ}\text{C}$) | $-30 \sim +80$ |
| Housing | PPO plastic resin (Color: Black) |
| Leading Pin | Tin Plated Brass |
| Weight (Grams) | 1.3 |
| Condition by wave soldering ($^{\circ}\text{C}$) | 260 ± 5 / within 5 sec |
| Condition by hand soldering ($^{\circ}\text{C}$) | 350 ± 20 / within 5 sec |
| Options | For other options contact factory |

Dimensions: (units: mm)**PS: Vp-p = 1/2duty, square wave****RoHS Compliant**