



Mallory Sonalert Products, Inc.

Part #: **ZT028LAIC3G**

Sales Outline Drawing

Revision: **D**

Specifications:

INDIVIDUAL CONTROL OF LIGHT AND SOUND

| Function | LIGHT | SOUND |
|-----------------------|---|---------------------------------|
| Sound Level Category | N/A | Loud |
| Mode of Operation | Continuous | Slow Pulse @ 1 PPS |
| Lens Color | Opaque White | N/A |
| LED Color | GREEN | N/A |
| Rated Voltage | 24 VAC/DC | 24 VAC/DC |
| Voltage Range | 20 to 28 VAC/DC | 20 to 28 VAC/DC |
| Power Connection | L+ to +VAC/DC & L- to -VAC/DC | S+ to +VDC/VAC & S- to -VDC/VAC |
| Current Draw | 25mA MAX | 25mA MAX |
| Frequency | N/A | 3900 ± 500 Hz |
| Loudness @ 2 FT | N/A | 85 to 95 dB(A) Typ. |
| Housing Material | 6/6 Nylon, Color: Black | |
| Front Cap Material | 6/6 Nylon, Color: Opaque White | |
| Storage Temperature | -40° to +80° C | |
| Operating Temperature | -30° to +65° C | |
| Panel Mounting | Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole. | |
| Knurled Nut | Used to attach part to panel. The max recommended torque is 10 in-lbs. | |
| Weight (Typical) | 28 g | |
| NEMA 3R, 4X, & 12 | Approved with use of included gasket. | |
| Options | Please contact factory. | |

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

PATENT NUMBER 9165440
9576442

L- and S- are internally connected and only one must be connected.

