Mallory Sonalert Products, Inc.				Part #:	J٦	T028-YG-CSL	
Sa	les Outline	Drawing		Revision:	D		
pecifications:							
Stack Number:	1	2	1	1		1	
LED Color:	YELLOW	GREEN		+			
Connection Wires:	Yellow and Brown	Green and Brown		1			
LED Current Draw:	<60 mA	<40 mA	241142/22	ļ.			
Rated Voltage:			24 VAC/DC				
Operating Voltage:		1	20-28 VAC/D	C			
Sound Level Category:	Loud	Loud	Loud			Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	•	Continuous	for 5 sec then 0.1s beep up reset	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Gr	to Green/Yellow wires connected to Green/Yellow			
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max	•		40mA Max.	
Loudness @ 1m:	TOTAL WILLY.	TOTAL WAY	80-85 dB(A) Ty		1	701111 (1710)	
Frequency:			2000 ± 500 H				
Total Max Current:		.4.40			rkina		
		<140mA with all LED's and sound unit working					
Operating Temperature:			-25° ~ +60°C				
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole						
Weight Typical (g):	685						
NEMA 12:	Approved						
Options:							
mensions: Inches (m	m) PATENT N	cUL Recogr NUMBER D898600	Please contact far nized 10309594	ctory.		ROHS Complia	
mensions: Inches (m	,		nized		KET	ROHS Complia	
mensions: Inches (m	PATENT	NUMBER D898600	nized	ctory.	KET	ROHS Complia	
mensions: Inches (m	PATENT		nized 10309594	GAS.	Ø0.57 [Ø1.2 for wire 2.04 [4.61 es 51.91	
## Sions: Inches (m	T STACK COLOR WIR	E TO POWER AND BED BLACK WIRES TO I	#10 or Smm screws for mounting 0.95 [24.	GAS. [Ø5.2] aces MOUNTII DIAGRAI	0.57 [ø]. for wire 2.04 [0.95 [24]	4.61 es 51.91	
TOP VIEW Inches (m 5.2 [132.0] YELLOW GREEN 2.4 [61.8	T STACK COLOR WIR	E TO POWER AND BED BLACK WIRES TO E, CONNECT GRAY &	10309594 10309594 #10 or 5mm screws for mounting 0.95 [24.]	GAS. [Ø5.2] .oces MDUNTII DIAGRAI	0.57 [ø]. for wire 2.04 [0.95 [24]	4.61 25 51.91	