



1 2 3 4 5 6 7



MSW P/N	Length	⑧ PE BAG	⑨ PE BAG
AK-CHMF-2	2000±50	130*230*0.05mm	280*330*0.05mm
AK-CHMF-015	1500±30	100*200*0.05mm	230*300*0.05mm
AK-CHMF-025	2500±50	130*230*0.05mm	280*330*0.05mm
AK-CHMF-050	5000±50	180*280*0.05mm	330*380*0.05mm

Electrical test:
 1. 100% short, open, miss wire test
 2. Conduct resistance:5 Ohm(max)
 3. Insulation resistance:5Mohm(mIn)
 4. dielectric test:DC 300V

PIN ASSIGNMENT:



⑩	TIE	2	BLACK
⑨	PE BAG	1/10	CLEAR PRINT BLACK*MADE IN CHINA*+*10PCS*
⑧	PE BAG	1	CLEAR PRINT BLACK*MADE IN CHINA*+*1PC*
⑦	TUBE	4	HEAT SHRINK TUBE BLACK OD1.5*10mm
⑥	IN JACKET	3.2g	CLEAR LD-PE(Mould NO.NM-006)
⑤	OUT JACKET	6.6g	PVC-40P RED(RD-35)
④	OUT JACKET	6.6g	PVC-40P WHITE(W-100)
③	CABLE	1	NOUL (10/0.10+28/0.10)*2F JACKET BLACK OD2.8*5.6mm
②	CONN	2	RCA PLUG FEMALE NI-PLATED INSULATOR COLOR:BROWN
①	CONN	2	RCA PLUG MALE BLOSSOM TYPE NI-PLATED INSULATOR COLOR:BROWN

RoHS compliant
 Unit: mm

Scale	Free	Customer-No.	
TOLERANCE		Drawn	20.02.2017 Amy
		Approved	20.02.2017 Amy
DIM	TOL	ASSMANN WSW-No. AK-CHMF-XX	
		Drawing-No. ASS 7865 CA	
Angle	TOL	Replace Sheet	
		rev00	
Id.	⑩ Drawn	Date 20.02.2017 Name Amy	
Modification		Date 20.02.2017 Name Amy	



1 2 3 4 5 6 7

A B C D E F G H