Specification Sheet

Part Number: GT.50X8MP2V2



UL 94 V-2 flame rated material allows use in air handling spaces. Features quick release for repetitive access to cable and wire.

Can be opened and closed numerous times without failure.

Adjustable so one size can accommodate multiple bundle diameters.

Grip Tie, UL94V0-2 Flame Rated, .5" x 8.0", PA6/PP, Maroon, 10/pkg

Article Number	854-44368
Type	GT.50X8
Color	Red Brown (RDBN)
Quantity Per	bag
Product Description	HellermannTyton offers UL 94 V-2 flame rated Grip Ties for use in air handling spaces. Grip Ties are UL Listed in accordance with the National Electric Code regulations. Grip Ties are low-profile, one-piece fastening devices. Constructed of a hook and loop design, laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.
Short Description	Grip Tie, UL94V0-2 Flame Rated, .5" x 8.0", PA6/PP, Maroon, 10/pkg

Global Part Name	GT.50X8
Minimum Tensile Strength (Imperial)	40.0
Minimum Tensile Strength (Metric)	177.93
Length L (Imperial)	8.0
Length L (Metric)	203.2
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Max (Imperial)	1.91
Bundle Diameter Max (Metric)	48.514
Material	Polyamide 6 (PA6) Polypropylene (PP)
Material Shortcut	PP PA6
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3926909988

© 2022 HellermannTyton. All Rights Reserved.