HellermannTyton

Specification Sheet

Part Number: MCRI-BS

Raceway and fittings are manufactured from a UL 94V-0 rated material to insure compliance with codes

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard

Raceway and fittings are U.L. Listed to 600 Volts to meets new UL5A and CSA 22.2 No. 62-93 standards



Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables

InfoStream Multi-Channel Raceway Base Splice, PVC, Ivory, 10/pkg

Article Number 250-00033

Type MCR-BS

Color Ivory (IV)

Quantity Per bag

Product Description HellermannTyton's InfoStream non-metallic raceway system can

accommodate up to four separate channels of electrical, voice, data, video or fiber optic cabling. The elliptical shape is aesthetically pleasing when compared to other designs. The raceway's unique and

patented design make installations quicker and easier.

Short Description InfoStream Multi-Channel Raceway Base Splice, PVC, Ivory, 10/pkg

Global	Part	Name
Olobai	ı aıı	Hallic

MCR-BS-PVC-BGE

Width W (Imperial)

4.5

Width W (Metric)

114.3

Height H (Imperial)

2.05

Height H (Metric)

52.07

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability

UL 94 V-0

Halogen Free

No

Operating Temperature

+122°F (+50°C)

Reach Compliant (Article 33)

No

ROHS Compliant

Yes

UL Listed (US and Canada)

Yes

UL Listed (US)

Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 3925900000

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions