

## Specification Sheet

Part Number: 553-50078

Slide Slit and optional center slits for easy wire insertion.  
Smooth surface for clean and legible printing.

Supplied on a ladder style carrier so that markers can be kitted after printing.



A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

ShrinkTrak Labels, 1-Sided, Unslit, .125" (3.17mm), PO-X, White, 2500/box

**Article Number** 553-50078

**Type** HST3-1WH

**Color** White (WH)

**Quantity Per** box

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** ShrinkTrak Labels, 1-Sided, Unslit, .125" (3.17mm), PO-X, White, 2500/box

**Global Part Name** HST3-1WH-PO-X-WH

**Variant** Thin-Wall

**Width W (Imperial)** 1.9

**Width W (Metric)** 48.26

**Thickness T (Imperial)** .003

**Thickness T (Metric)** .0762

**Height H (Imperial)** 0.235

**Height H (Metric)** 5.69

**Width of Liner (Metric)** 76.2

**Width of Liner (Imperial)** 3.0

**Outside Diameter OD (Imperial)** 0.125

**Outside Diameter OD (Metric)** 3.2

**Outside Diameter Max (Imperial)** 0.125

**Outside Diameter Max (Metric)** 3.2

**Wall Thickness WT (Imperial)** 0.031

**Wall Thickness WT (Metric)** 0.79

<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Material Shortcut</b>	PO-X
<b>US MIL SPEC</b>	SAE-AS81531 SAE-AMS-DTL-23053/5 Class 1 and 3 MIL-STD-202G Method 215K
<b>Flammability</b>	UL 224 VW-1
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-67°F to +275°F (-55°C to +135°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	CEN
<b>Package Quantity (Imperial)</b>	2500
<b>Package Quantity (Metric)</b>	2500
<b>Customs Number</b>	3917320000
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)