

## Specification Sheet

Part Number: TAG21J-450



Ink jet printable polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.

When used with black pigment-based inks, the material can withstand chemicals and solvents.

Inkjet Label, .75" x .5", 156 Per Sheet, PET, White, 5000/pkg

**Article Number** 593-21450

**Type** TAG21J

**Color** White (WH)

**Quantity Per** pack

### Product Description

HellermannTyton offers a series of technologically advanced labels for use on standard inkjet printers. The labels come on 8.5" x 11" sheets and are printable using HellermannTyton's TagPrint Pro software. A wide range of materials and sizes is available for wire and component marking. When used with pigment based inks, HellermannTyton inkjet labels offer superior non-smear marks that are chemical and solvent resistant. Even colors can be printed when used on a color inkjet printer. Inkjet labels are available in polyester or paper.

<b>Short Description</b>	Inkjet Label, .75" x .5", 156 Per Sheet, PET, White, 5000/pkg
<b>Global Part Name</b>	TAG21J-450-WH
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	0.75
<b>Height H (Metric)</b>	19.05
<b>Material</b>	Type 450, Polyethylene Terephthalate (450)
<b>Material Shortcut</b>	450
<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Compliant (Article 33)</b>	Yes

<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Customs Number</b>	3919905060
<b>Labels per Column</b>	12
<b>Labels per Row</b>	13

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)