

Specification Sheet

Part Number: T120S0K2



- Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail allows for simpler insertion.

Heavy Duty Cable Tie, 9" Long, UL Rated, 120lb Tensile Strength, PA66, Black, 50/pkg

Article Number	111-12803
Type	T120S
Color	Black (BK)
Quantity Per	bag
Product Description	Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy Duty Cable Tie, 9" Long, UL Rated, 120lb Tensile Strength, PA66, Black, 50/pkg

Global Part Name	T120S-PA66-BK
-------------------------	---------------

Minimum Tensile Strength (Imperial)	120.0
--	-------

Minimum Tensile Strength (Metric)	535.0
--	-------

Length L (Imperial)	9.0
----------------------------	-----

Length L (Metric)	225.0
--------------------------	-------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.30
---------------------------	------

Width W (Metric)	7.6
-------------------------	-----

Bundle Diameter Min (Imperial)	0.20
---------------------------------------	------

Bundle Diameter Min (Metric)	5.0
-------------------------------------	-----

Bundle Diameter Max (Imperial)	2.17
---------------------------------------	------

Bundle Diameter Max (Metric)	55.0
-------------------------------------	------

Thickness T (Metric)	1.6
-----------------------------	-----

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)