

## Specification Sheet

Part Number: MB19M4



Compact size for areas with limited mounting space.  
Simple to install with a screw or rivet.

Single hole attachment with two-way entry for cable tie.

Cable Tie Anchor Mount, .50" x .312", .13" Hole Dia, .1" Max Tie Width, PA66, Natural, 1000/pkg

**Article Number** 151-00294

**Type** MB1

**Color** Natural (NA)

**Quantity Per** bag

**Product Description** These cable tie mounts are compact in size. They are designed for simple yet robust installation particularly in areas with limited space. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets.

**Short Description** Cable Tie Anchor Mount, .50" x .312", .13" Hole Dia, .1" Max Tie Width, PA66, Natural, 1000/pkg

**Global Part Name** MB1-PA66-NA

<b>Length L (Imperial)</b>	0.5
<b>Length L (Metric)</b>	12.7
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.312
<b>Width W (Metric)</b>	7.92
<b>Cable Ties</b>	T18
<b>Height H (Imperial)</b>	.13
<b>Height H (Metric)</b>	3.30
<b>Cable Tie Width Max (Imperial)</b>	0.1
<b>Cable Tie Width Max (Metric)</b>	2.54
<b>Mounting Hole Diameter D (Imperial)</b>	0.13
<b>Mounting Hole Diameter D (Metric)</b>	3.3 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	3.3
<b>Material</b>	Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988