

## Specification Sheet

Part Number: WSM60IMHSUVH1



Design makes installation along frame rails fast and easy  
Using weld stud eliminates the need for grinding down painted surfaces  
which saves time

Weld Stud eliminates need for stocking multiple sized metal P-Clamps  
which saves time and cost

Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

**Article Number** 151-00146

**Type** WSM60

**Color** Black (BK)

**Quantity Per** bag

**Product Description** When used in conjunction with a cable tie, the Weld Stud Mount significantly reduces time and labor, and eliminates the need for multiple sized P-clamps, nuts, and bolts. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation. Adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

<b>Short Description</b>	Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg
<b>Global Part Name</b>	WSM60-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.32
<b>Length L (Metric)</b>	33.5
<b>Width W (Imperial)</b>	1.07
<b>Width W (Metric)</b>	27.2
<b>Height H (Imperial)</b>	1.06
<b>Height H (Metric)</b>	27.0
<b>Stud Diameter (Metric)</b>	6.0 mm
<b>Stud Diameter (Imperial)</b>	0.24
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)

<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988