

Specification Sheet

Part Number: MB5A0C2

For use with HellermannTyton T18 - T150 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 2.1 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 100/pkg

Article Number 151-28602

Type MB5A

Color Black (BK)

Quantity Per bag

Product Description MB5A adhesive mounts are for use with HellermannTyton T18 - T150 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.

Short Description	Rubber Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 100/pkg
Global Part Name	MB5A-PA66-BK
Length L (Imperial)	1.49
Length L (Metric)	37.7
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	1.49
Width W (Metric)	37.7
Cable Ties	T18 - T150
Height H (Imperial)	.28
Height H (Metric)	7.1
Cable Tie Width Max (Imperial)	0.35
Cable Tie Width Max (Metric)	8.9
Mounting Hole Diameter D (Imperial)	0.19
Mounting Hole Diameter D (Metric)	4.8 mm
Mounting Hole Diameter D Max (Metric)	4.8

Mounting Hole Centers (Imperial) 1.0

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Synthetic rubber with base of polyethylene foam

Flammability UL 94 V-2 (excluding adhesive)

Adhesive Operating Temperature 0°F to +150°F (-18 °C to +66 °C)

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988

