

Specification Sheet

Part Number: 596-00851

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

| PHOTOVOLTAIC SYSTEM DC DISCONNECT | |
|--------------------------------------|----------------------|
| OPERATING CURRENT: | <input type="text"/> |
| OPERATING VOLTAGE: | <input type="text"/> |
| MAXIMUM SYSTEM VOLTAGE: | <input type="text"/> |
| SHORT CIRCUIT CURRENT: | <input type="text"/> |

Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 10/pkg

| | |
|-----------------------|------------|
| Article Number | 596-00851 |
| Type | DCRATING10 |
| Color | Red (RD) |
| Quantity Per | pack |

| | |
|-------------------------------|---|
| Product Description | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014 and 2017 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014 and 2017 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| Short Description | Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 10/pkg |
| Global Part Name | DCRATING10-840/281-RD |
| Technical Description | Printable Solar Label, DC RATING LABEL, 3.75" X 2.0", Red |
| Local Order Number 2 | Cross Reference = 50 per roll: 596-00241; Printable Metal Solar Placard 5 pack: 596-00864; Engravable Metal Solar Placard 5 pack: 596-00865 |
| Width W (Imperial) | 3.75 |
| Width W (Metric) | 92.25 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 2.0 |
| Height H (Metric) | 50.80 |

| | |
|---------------------------------------|--|
| Material | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut | 840/281 |
| Adhesive | Acrylic |
| Halogen Free | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | CSA 66956 NEC2014 NEC2011 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 3919905060 |
| Labels per Column | 1 |

