

## Specification Sheet

Part Number: SAM83HIRHSH1



Positions bundles off cross members and frame rails to prevent abrasion and chafing.

Metal insert bushing accommodates high-torque installation.

Made with high-impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.

Axial Oval Mount, .31" (8mm) Mounting Hole, PA66HIRHS, Gray, 500/pkg

**Article Number** 151-29600

**Type** SAM83

**Color** Gray (GY)

**Quantity Per** bag

**Product Description** HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.

**Short Description** Axial Oval Mount, .31" (8mm) Mounting Hole, PA66HIRHS, Gray, 500/pkg

**Global Part Name** SAM83-PA66HIRHS-GY

<b>Length L (Imperial)</b>	1.40
<b>Length L (Metric)</b>	34.0
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	1.0
<b>Width W (Metric)</b>	26.0
<b>Cable Ties</b>	T50 - T250
<b>Height H (Imperial)</b>	1.40
<b>Height H (Metric)</b>	35.0
<b>Cable Tie Width Max (Imperial)</b>	0.5
<b>Cable Tie Width Max (Metric)</b>	12.7
<b>Mounting Hole Diameter D (Imperial)</b>	0.31
<b>Mounting Hole Diameter D (Metric)</b>	8.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.31
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.31
<b>Mounting Hole Diameter D Max (Metric)</b>	8.0
<b>Stud Diameter (Metric)</b>	8.0 mm

<b>Stud Diameter (Imperial)</b>	0.3125
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988