TINA-WW

~60° wide beam optimized for CREE XP-E. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16.1 mm
Height	9.7 mm
Fastening	tape
ROHS compliant	yes

MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
TINA-WW-XP	Single lens	PMMA	clear	
TINA-XP-H-TAPE-WHT	Holder	PC	white	
TINA-TAPE3	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FA11019_TINA-WW	Single lens	2016	288	144	4.1
» Box size:					

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



Isometric view



Bottom view



Front view

MATERIALS
Lens: PMMA
Holder: PC
Tape Acrylic foam

Part No.s:
FA11019_Tina-WW-XP
FA11019_Tina-WW-XP-G
FA11019_Tina-WW-Z5

This drawing is our property.
It can't be reproduced
or communicated without
our written agreement.

Ledil Oy
Tehdaskatu 13
FIN-24100 SALO
Finland

DRAWN BY: mav	DATE: 09.03.2011	DRAWING TITLE: Assembly Tina-XP WW			
CHECKED BY: tk	DATE: 09.03.2011	SIZE: A4	DRAWING NUMBER: FA11019		REV: 2
DESIGNED BY: HH	DATE: 22.07.2008	SCALE: 2:1	WEIGHT(g): -		SHEET: 1/1

See also our general installation guide: www.ledil.com/installation_guide

PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	XP-E
FWHM / FWTM	58.0° / 94.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

CREE LED

LED	XP-G
FWHM / FWTM	62.0° / 106.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	35.0° / 79.0°
Efficiency	92 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LUMILEDS

LED	LUXEON Z ES
FWHM / FWTM	29.0° / 78.0°
Efficiency	91 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NCSxE17A
FWHM / FWTM	23.0° / 66.0°
Efficiency	86 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SAMSUNG

LED	LH351B
FWHM / FWTM	67.0° / 98.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

CREE LED

LED	XT-E
FWHM / FWTM	52.0° / 102.0°
Efficiency	%
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z5
FWHM / FWTM	33.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.