www.lemo.com

# BRA.2B.200.PCSG

## SUMMARY

**# Wires**



*Image is for illustrative purpose only*

| | |
|---|---|
| **Series** | 2B |
| **Termination type** | No contacts / Accessory |
| **IP rating** | 61 |
| **AWG wire size** | 0.00 - 0.00 |
| **Cable Ø** | 0.00 - 0.00 mm |
| **Status** | active |

### Download

Request a quote

Catalog

## TECHNICAL DETAILS

### Mechanics

| | |
|---|---|
| **Shell Style/Model** | BRA*: Cap for receptacle |
| **Keying** | No keying |
| **Housing Material** | POM (Polyoxymethylene) shell without treatment, silicone gasket |
| **Weight** | 1.24 g |

### Performance

**Configuration**

**Insulator**

**Rated Current**


### Others

Endurance (Shell): 5000
Temp (min / max): -55°C / +100°C
Humidity (max): <=95% [at 60 deg C /140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [ 6 ms]

*LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*

Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)

# DRAWINGS




No keying

### Dimensions

| | A | B | L | M | N |
|---|---|---|---|---|---|
| mm. | 18 | 21 | 14.5 | 6 | 60 |
| in. | 0,71 | 0,83 | 0,57 | 0,24 | 2,36 |

# RECOMMENDED BY LEMO

### Tools

*LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*