

## Specification Sheet

Part Number: 556-26008



Halogen Free for low smoke and low fire hazard applications.  
White front and yellow back for versatility.

Superior strength and tear resistance for long lasting identification.

Pre-cut slots to secure the TipTags using HellermannTyton cable ties.

TipTag, 2.59" x .68", PO/Polyester, White/Yellow, 500/roll

<b>Article Number</b>	556-26008
-----------------------	-----------

<b>Type</b>	TIPTAGVA15X65YEWB
-------------	-------------------

<b>Color</b>	Yellow (YE) White (WB)
--------------	------------------------

<b>Quantity Per</b>	pack
---------------------	------

<b>Product Description</b>	TIPTAGs are halogen free, tear resistant, and lightweight cross laminated polyolefin tags ideal for use where weight is a critical factor. Each side is a different color. One side is yellow and the other side is White so that a high contrast black on yellow or black on white mark can be printed.
----------------------------	--

<b>Short Description</b>	TipTag, 2.59" x .68", PO/Polyester, White/Yellow, 500/roll
--------------------------	--

<b>Global Part Name</b>	TIPTAGVA15X65YEWB-PO-WB/YE
-------------------------	----------------------------

<b>Fixation Method</b>	Others
<b>Variant</b>	Other
<b>Width W (Imperial)</b>	2.59
<b>Width W (Metric)</b>	65.0
<b>Height H (Imperial)</b>	0.68
<b>Height H (Metric)</b>	17.4
<b>Material</b>	Polyolefin (PO)
<b>Material Shortcut</b>	PO
<b>US MIL SPEC</b>	SAE-AS81531 MIL-STD-202G Method 215K
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-58°F to +221°F (-50°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	CEN BS-4G-198-3, Type 11a

<b>Package Quantity (Imperial)</b>	500
------------------------------------	-----

<b>Package Quantity (Metric)</b>	500
----------------------------------	-----

<b>Customs Number</b>	3921905050
-----------------------	------------