HellermannTyton

Specification Sheet

Part Number: MCRFW-RDB



Raceway and fittings are manufactured from a UL94 V0 rated material to ensure compliance with codes.

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard.

Raceway and fittings are UL Listed to 600 Volts to meet new UL5A and CSA 22.2 No. 62-93 standards.

InfoStream Multi-Channel Raceway Raised Device Bracket Fitting, PVC, Office White, 10/pkg

Article Number	250-00025
Туре	MCR-RDB
Color	Office White (OEWH)
Quantity Per	bag
Product Description	Raised device bracket is used to mount NEMA standard single gang device and faceplate. Raised bracket allows for additional wire fill space and additional device clearance. Use with side divider for 2-channel applications.
Short Description	InfoStream Multi-Channel Raceway Raised Device Bracket Fitting, PVC, Office White, 10/pkg

Global Part Name

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V-0
Halogen Free	No
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	3925900000

© 2021 HellermannTyton. All Rights Reserved.