

Fuse DTI 250V



See below:
[Approvals and Compliances](#)

Description

- Operation full range cable defensive fuses
- Over-load and short-circuit protection
- Colored characteristic detector in the middle
- Characteristic gG
- According to SEV 1010

Technical Data

Rated Current In	4- 16A
Rated Voltage	250 VAC
Breaking Capacity	10kA
Rated Power Operating Frequency fe	50Hz

Basic Design

Insulator	Ceramics
Metal components	Brass

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Time-Current-Curves

DT I



Current in Amperes

All Variants

Rated current	Color	Packaging unit	Order Number	E-No.
[A]		Pcs		
4	brown	25	0001.2002	800150409
6	green	25	0001.2011	800150609
10	red	25	0001.2012	800151009
16	grey	25	0001.2005	800151509

Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>