

DIN-Signal coax f, solder/crimp, 75Ohm



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 03 000 6281 |
| Specification | DIN-Signal coax f, solder/crimp, 75Ohm |
| HARTING eCatalogue | https://b2b.harting.com/09030006281 |

Identification

| | |
|----------------------------|---|
| Category | Contacts |
| Series | DIN 41612 |
| Type of contact | Coaxial contact |
| Description of the contact | Straight |
| Contacts for | DIN 41612 Type M |
| | DIN 41612 Type MH 21+5 |
| | DIN 41612 Bauform M 0+2 |
| | har-modular [®] M module, male, angled |
| | har-modular [®] M module, male, straight |

Version

| | |
|-----------------------|------------------------------------|
| Termination method | Solder/crimp termination |
| Gender | Female contact for male connectors |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|-----------------------|---|
| Operating current | ≤0.4 A |
| Rated voltage | 250 V |
| Insulation resistance | >10 ⁹ Ω |
| Contact resistance | ≤10 mΩ for inner contact die ≤3 mΩ for outer ferrule |
| Impedance | 75 Ω |
| Limiting temperature | -55 ... +125 °C |
| Return loss | >19 dB @ 1 GHz for cables RG 179 |
| | >14 dB @ 2 GHz for cables RG 179 |



Technical characteristics

| | |
|---------------------------|---------|
| Insertion force | ≤10 N |
| Withdrawal force | ≥1 N |
| Performance level | 1 |
| Mating cycles | ≥500 |
| Test voltage $U_{r.m.s.}$ | 0.75 kV |
| Frequency | 2 GHz |

Material properties

| | |
|--------------------------------------|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni Mating side |
| Material (locking) | Copper alloy |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | ecef7555-f643-4ceb-a337-fc54762297f1 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Lead |

Specifications and approvals

| | |
|----------------|-----------|
| Specifications | DIN 41626 |
|----------------|-----------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 40 |
| Net weight | 1.907 g |
| Country of origin | Czechia |
| European customs tariff number | 85366990 |
| eCl@ss | 27440204 Contact for industrial connectors |

Assembly instructions

