

Ideal for enclosures with perforated doors (not for use in enclosures with solid/plexiglass/glass doors) Install the unit using a bottom-mounting configuration only, with the enclosure's floor open and no tray or pan below the SRCOOL7KRM evaporator coils can be vented through enclosure's rear perforated doors or optional SRCOOL7KDUCT (no solid doors) In an open frame application, cooling air delivered to the equipment is lessened, since cold air escapes into the room. Condenser must be ducted using the SRCOOL7KDUCT.

AC Unit for Server Racks - Rack Mount, 7,000 BTU (2.0 kW), 120V, 8U

MODEL NUMBER: SRCOOL7KRM



The SRCOOL7KRM is the first EIA-compliant rack-mounted server rack cooling system specifically designed to cool IT equipment in data centers, server rooms and network closets.

Description

The SRCOOL7KRM Rack-Mounted Server Rack Air Conditioner pumps 7,000 BTU/h (2.0 kW) of close-coupled cooling power into your IT equipment to prevent shutdowns, malfunctions and failures caused by overheating. This space-saving, energy-efficient unit is perfect for data centers, server rooms, network closets and other environments with heat-sensitive rack-mounted equipment and limited floor space. The self-contained SRCOOL7KRM mounts just like any other rack equipment in 8U of space at the bottom of a rack enclosure. A magnetic air dam attaches to the front door of the rack enclosure to ensure that equipment draws cool air from the SRCOOL7KRM instead of drawing warm air from the room. Because it only cools the equipment inside the rack enclosure, the SRCOOL7KRM is much more efficient than solutions that cool an entire room to achieve the same result. The SRCOOL7KRM filters the air, and its built-in evaporator eliminates condensation, as well as the need for a floor drain or water collection tank.

The 7-ft. (2.13 m) cord plugs into a standard 15A (NEMA 5-15R) outlet. The unit restarts automatically after power failures, and you can use the built-in timer to schedule unattended shutdown and startup. The intuitive control panel includes a digital display and diagnostic LEDs to communicate operating conditions at a glance.

The optional SRCOOLNET2LX remote management accessory (sold separately) allows you to monitor temperatures, receive alerts, review logs and control settings over the Ethernet network from any location via SNMP, Web, SSH or telnet. The SRCOOLNET2LX accessory also includes an ENVIROSENSE® temperature and humidity sensor that allows you to link cooling output with temperature readings up to 12 feet away.

Features

Compact and Efficient Cooling Saves valuable floor space in IT environments with available space at the bottom of a rack Saves energy with efficient close-coupled cooling, cooling only the equipment inside the rack enclosure instead of the entire room Provides 7,000 BTU/h (2.0 kW) of cooling capacity in a rack-

Highlights

- Saves valuable floor space in IT environments
- Saves energy with efficient close-coupled cooling
- Provides 7,000 BTU/h (2.0 kW) of cooling capacity
- Supports optional remote management via Ethernet
- Mounts at the bottom of an EIA-standard 19 in. rack

Package Includes

- SRCOOL7KRM SmartRack Rack-Mounted Server Rack Cooling Unit - 7,000 BTU, 120V
- Magnetic air dam kit
- Directional output vent
- Mounting hardware
- Owner's manual



mounted 8U chassis Prevents equipment shutdowns, malfunctions and failures caused by overheating and temperature fluctuations Uses environmentally friendly R410A refrigerant

Convenient Operation Directional output vent aims air upward to cool overheated rack equipment Supports unattended shutdown and startup, including automatic restarts after power failures Intuitive front-panel controls with an informative digital display and diagnostic LEDs Operates at noise levels comparable to an average office setting

Remote Management Support Optional SRCOOLNET2LX remote management accessory (sold separately) allows you to monitor temperatures, receive alerts, review logs and control settings over the Ethernet network from any location via SNMP, Web, SSH or telnet SRCOOLNET2LX includes ENVIROSENSE temperature and humidity sensor that allows you to link cooling operation with temperature readings up to 12-ft. (3.66 m) away

Optional SRCOOL7KDUCT Exhaust Duct Kit Directs and disperses heat from SRCOOL7KRM through an upper vent into your facility's ventilation system Sold separately

Easy Installation Plugs into a standard 15A outlet (NEMA 5-15R) Built-in evaporator eliminates condensation—no floor drain or water collection tank needed Magnetic air dam attaches to rack enclosure's front door to optimize airflow Includes mounting hardware for installation at bottom of EIA-standard 19 in. rack enclosures

Specifications

| OVERVIEW | |
|------------------------------------|--|
| UPC Code | 037332184733 |
| INPUT | |
| Electrical Consumption (Max) | 1020 Watts Max |
| Nominal Input Voltage(s) Supported | 120V AC |
| Input Connection Type | NEMA 5-15P |
| Input Frequency | 60 Hz |
| Input Cord Length (ft.) | 7 |
| Input Cord Length (m) | 2.13 |
| COOLING | |
| Cooling Type | Active |
| Airflow | 198.25 CFM |
| Cooling Capacity (BTUs) | 7000 |
| Cooling Capacity (kW) | 2.0 |
| Equivalent Room Size | 250 sq. ft. (25 sq. m) |
| Cooling Capacity | 7,000 BTU / 2.0 kW |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LCD Display | 2-digit LCD displays numerical temperature readout |



| | |
|--------------------------------------|---|
| Front Panel LEDs | Push-button control panel with multiple LEDs for operational configuration |
| PHYSICAL | |
| Color | Black |
| Form Factors Supported | Rackmount |
| Rack Height | 8U |
| Shipping Dimensions (hwd / cm) | 57.91 x 57.66 x 69.85 |
| Shipping Dimensions (hwd / in.) | 22.80 x 22.70 x 27.50 |
| Shipping Weight (kg) | 36.29 |
| Shipping Weight (lbs.) | 80.00 |
| Unit Dimensions (hwd / in.) | 13.9 x 17.35 x 22.52 |
| Unit Dimensions (hwd / cm) | 35.3 x 44.1 x 57.2 |
| Unit Weight (lbs.) | 61.6 |
| Unit Weight (kg) | 27.94 |
| COMMUNICATIONS | |
| SNMP Compatibility | SRCOOLNET2LX ; (Optional) remote management accessory for remote monitoring and control |
| FEATURES & SPECIFICATIONS | |
| Dehumidifier | 1.25L / hour |
| Compressor Type | Rotary |
| Refrigerant | R410a (Environmentally friendly, Non ozone depleting) |
| Refrigerant Amount | 18.7 ounces |
| Amp Draw Nominal | 8.5 |
| Sound Level (Noise) | 57dbA |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to UL484; CSA, RoHS; NOM |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>